

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

AZOLLA AL 32

SDS #: 37062

Date of previous revision : 2021/04/21

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: AZOLLA AL 32

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Hydraulic oil

Formulation additives, lubricants and greases - Industrial General use of lubricants and greases in vehicles or machinery - Industrial General use of lubricants and greases in vehicles or machinery - Professional

1.3 Details of the supplier of the safety data sheet

VotalEnergies Lubrifiants562 Avenue du Parc de L'ile92029 Nanterre Cedex FRANCETél: +33 (0)1 41 35 40 00Fax: +33 (0)1 41 35 84 71m.msds-lubs@totalenergies.com

See section 16 to have the contact details of the local supplier

Contact

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number	 France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59 In France - Poison centers: ANGERS : 02 41 48 21 21 BORDEAUX : 05 56 96 40 80 LILLE : 08 00 59 59 59 LYON : 04 72 11 69 11 MARSEILLE : 04 91 75 25 25 NANCY : 03 83 22 50 50 PARIS : 01 40 05 48 48 STRASBOURG : 03 88 37 37 37
	TOULOUSE : 05 61 77 74 47
<u>Supplier</u>	
T - 1 1 1	- England and the second 44 4005 000070



SDS # : 37062

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2	Label	elements

Signal word	: No signal word.
Hazard statements	: H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: P273 - Avoid release to the environment.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.

Not available.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %. This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

Other hazards which do : Mone known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures Product/substance	: Mixture	% (w/w)	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
 Fydrocarbons, C15-C20, n- alkanes, isoalkanes, cyclics, < 0.03% aromatics 		≥50 - ≤75	Asp. Tox. 1, H304	-	[1]
2,6-di-tert-butyl-p-cresol	REACH #: 01-2119555270-46 EC: 204-881-4	≤1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1] [2]



SDS #: 37062

methanol	CAS: 128-37-0 EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	<0.1	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (vapours)] = 3 mg/l STOT SE 1, H370:	[1] [2]
			See Section 16 for the full text of the H statements declared above.	C ≥ 10% STOT SE 2, H371: 3% ≤ C < 10%	

Additional information

: Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346 The product is made from synthetic base oils

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

1 Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

The EC substance definition and related classification & labelling have been developed in the framework of the Regulation (EC) No 1907/2006 (REACh). The related CAS number* is used for the purpose of the international inventories present in section 15 of the SDS.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures : Immediately flush eves with plenty of water, occasionally lifting the upper and lower Eve contact evelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs. Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Skin contact : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse. : Wash out mouth with water. Remove dentures if any. If material has been Ingestion swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. 4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data.

Revision:2022/10/28	Version : 2
---------------------	-------------



Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.
4.3 Indication of any imr	nediate medical attention and special treatment needed
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

U	-
5.1 Extinguishing media	
Suitable extinguishing media	Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	Do not use water jet.
5.2 Special hazards arising f	n the substance or mixture
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	 Farbon monoxide carbon dioxide nitrogen oxides phosphorus oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection fo chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures : No action shall be taken involving any personal risk or without suitable training. For non-emergency Evacuate surrounding areas. Keep unnecessary and unprotected personnel from personnel entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". 6.2 Environmental : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused precautions environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.



6.3 Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)Recommendations: Not available.Industrial sector specific: Not available.solutions

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits



Product/substance	Exposure limit values
2,6-di-tert-butyl-p-cresol	Ministry of Labor (France, 5/2021). Notes: Permissible limit values (circulars)
	TWA: 10 mg/m ³ 8 hours.
methanol	Ministry of Labor (France, 5/2021). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of
	the Labor Code)
	TWA: 200 ppm 8 hours.
	TWA: 260 mg/m ³ 8 hours.
	Ministry of Labor (France, 5/2021). Absorbed through skin.
	Notes: Permissible limit values (circulars)
	STEL: 1000 ppm 15 minutes.
	STEL: 1300 mg/m ³ 15 minutes.

Reportable hazardous constituent(s) contained in UVCB and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Advisory OEL : Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH (TLV) TWA 5 mg/m3 (highly refined)

DNELs/DMELs

Product/substance	Туре	Exposure	Value	Population	Effects
2,6-di-tert-butyl-p-cresol	DNEL	Long term Dermal	0.25 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Dermal	0.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term	0.435 mg/	General	Systemic
		Inhalation	m³	population	
	DNEL	Long term Oral	0.25 mg/kg	General population	Systemic
	DNEL	Long term Oral	0.25 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.435 mg/ m ³	General population	Systemic
	DNEL	Long term Inhalation	1.76 mg/m ³	Workers	Systemic
methanol	DNEL	Short term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	4 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	20 mg/kg	Workers	Systemic



SDS # : 37062

		bw/day		
DNEL	Long term Dermal	20 mg/kg	Workers	Systemic
	_	bw/day		
DNEL	Short term	26 mg/m ³	General	Local
	Inhalation	-	population	
DNEL	Long term	26 mg/m ³	General	Local
	Inhalation	_	population	
DNEL	Short term	26 mg/m ³	General	Systemic
	Inhalation		population	
DNEL	Long term	26 mg/m ³	General	Systemic
	Inhalation		population	
DNEL	Short term	130 mg/m ³	Workers	Local
	Inhalation			
DNEL	Long term	130 mg/m ³	Workers	Local
	Inhalation			
DNEL	Short term	130 mg/m ³	Workers	Systemic
	Inhalation	_		
DNEL	Long term	130 mg/m ³	Workers	Systemic
	Inhalation			-

PNECs

Product/ingredient name	Compartment Detail	Name	Method Detail
2,6-di-tert-butyl-p-cresol	Fresh water	199 ng/l	-
	Marine water	19.9 ng/l	-
	Fresh water sediment	45819 µg/kg dwt	-
	Soil	53.9 µg/kg dwt	-
	Sewage Treatment Plant	17 µg/l	-
	Marine water sediment	45.82 µg/kg dwt	-
	Secondary Poisoning	16.67 mg/kg	-

8.2 Exposure controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
ures
: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.EN 166
: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.



SDS #: 37062

	Hydrocarbon-proof gloves nitrile rubber Fluorinated rubber
	 Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces. In case of inadequate ventilation wear respiratory protection: Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid. [limpid]
Color	: Colorless.
Odor	: Characteristic.
Odor threshold	: Not available.
рН	: Not applicable. Product is non-soluble (in water).
Melting point/freezing point	: 🔽 echnically not possible to measure
Initial boiling point and boiling range	: ₱316°C [ISO 3405]
Flash point	: Open cup: >130°C [Cleveland Open Cup (COC)]
Evaporation rate	: Not available.
Flammability	: Not applicable.
Lower and upper explosion limit	: Not available.
Vapor pressure	: 🕫 0.013 kPa [room temperature] Not applicable. [50°C]
Vapor density	: ▶2 [Air = 1]
Relative density	: 0.835 to 0.845 [ISO 12185]
Density	:



Solubility(ies)

Media		Result
water		Not soluble
Solubility in water	:	0
Miscible with water	:	No.
Partition coefficient: n-octanol/ water	:	Not applicable.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not applicable.
Viscosity	:	Kinematic (40°C): 29 to 35 mm²/s [ISO 3104]
Particle characteristics		
Median particle size	:	Not applicable.

9.2 Other information

No other relevant physical and chemical parameters for the safe use of the product

:

SECTION 10: Stabilit	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible materials	: Strong oxidizing agents
10.6 Hazardous decomposition products	: carbon monoxide carbon dioxide nitrogen oxides phosphorus oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
Hydrocarbons, C15-C20, n- alkanes, isoalkanes, cyclics, < 0.03% aromatics	LC50 Inhalation Dusts and mists	Rat	>5266 mg/m ³	4 hours	OECD 403
	LD50 Dermal	Rabbit	>3160 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
2,6-di-tert-butyl-p-cresol	LD50 Dermal	Rat	>2000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>6000 mg/kg	-	OECD 401
methanol	LC50 Inhalation Gas.	Rat	145000 ppm	1 hours	-
	LC50 Inhalation Gas.	Rat	64000 ppm	4 hours	-

Revision:2022/10/28	Version : 2	France	ENGLISH	9/23



LC50 Inhalation Vapor	Rat	3 mg/l	4 hours	-
LD50 Dermal	Rabbit	300 mg/kg	-	-
LD50 Oral	Rat	100 mg/kg	-	-

Conclusion/Summary :

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

	Product/substance	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
metha	anol	100	300	64000	3	N/A

Irritation/Corrosion

Product/substance	Result	Species	Score	Exposure	Test
2,6-di-tert-butyl-p-cresol	Eyes - Cornea opacity	Rabbit	0	-	OECD 405 Read across
	Skin - Edema	Rabbit	0	4 hours	OECD 404
Conclusion/Summary					

Skin	:	Based on available data, the classification criteria are not met.
Eyes	:	Based on available data, the classification criteria are not met.
Respiratory	:	Based on available data, the classification criteria are not met.
Sensitization		
Conclusion/Summary	:	
Skin	:	Based on available data, the classification criteria are not met.
Respiratory	:	Based on available data, the classification criteria are not met.
<u>Mutagenicity</u>		
Conclusion/Summary	:	Based on available data, the classification criteria are not met.
Carcinogenicity		
Conclusion/Summary	:	Based on available data, the classification criteria are not met.
Reproductive toxicity		
Conclusion/Summary	:	Based on available data, the classification criteria are not met.
<u>Teratogenicity</u>		
Conclusion/Summary	:	Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)		

Product/substance	Category	Route of exposure	Target organs
methanol	Category 1	-	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Conclusion/Summary : Based on available data, the classification criteria are not met.

Aspiration hazard

Product/substance	Result
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03 aromatics	% ASPIRATION HAZARD - Category 1
Conclusion/Summary : Based on available data, the o	lassification criteria are not met.



Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Defatting to the skin. May cause skin dryness and irritation.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the phys	sic	al, chemical and toxicological characteristics

Eye contact Inhalation	No specific data.No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information



SDS # : 37062

SECTION 12: Ecological information

Harmful to aquatic life with long lasting effects.

12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
ydrocarbons, C15-C20, n- alkanes, isoalkanes, cyclics, < 0.03% aromatics	Acute EC50 10000 mg/l	Algae - Skeletonema costatum	72 hours	ISO 10253
	Acute EC50 3193 mg/l	Daphnia - Acartia tonsa	48 hours	ISO 14669
	Acute LC50 1028 mg/l	Fish	96 hours	-
	Chronic NOELR >1000 mg/ I Marine water	Algae - Skeletonema costatum	21 days	-
	Chronic NOELR >1000 mg/ I Fresh water	Daphnia - Daphnia magna	21 days	-
	Chronic NOELR >1000 mg/ I Fresh water	Fish - Oncorhynchus mykiss	21 days	-
2,6-di-tert-butyl-p-cresol	Acute EC50 0.48 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute EC50 1440 µg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours	-
	Acute LC50 1.1 mg/l	Fish - Oryzias latipes	96 hours	OECD 203
	Chronic EC10 0.4 mg/l	Algae - Desmodesmus subspicatus	72 hours	OECD 201
	Chronic NOEC 0.07 mg/l	Daphnia - Daphnia magna	21 days	OECD 211
	Chronic NOEC 0.053 mg/l	Fish - Danio rerio	30 days	OECD 210
methanol	Acute EC50 16.912 mg/l Marine water	Algae - Ulva pertusa	96 hours	-
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours	-
	Acute LC50 3289 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours	-
	Acute LC50 290 mg/l Fresh water	Fish - Danio rerio - Egg	96 hours	-
	Chronic NOEC 9.96 mg/l Marine water	Algae - Ulva pertusa	96 hours	-

12.2 Persistence and degradability

Product/substance	Test	Result		Dose	Inoculum
₩ydrocarbons, C15-C20, n- alkanes, isoalkanes, cyclics, < 0.03% aromatics	OECD 306	74 % - Readily - 28		-	-
2,6-di-tert-butyl-p-cresol	OECD 301C	4.5 % - Not readily	- 28 days	-	Activated sludge
Conclusion/Summary	: Not available.				
Product/substance	Aquatic half-life	•	Photolysis	s	Biodegradability
	-		-		Readily
2,6-di-tert-butyl-p-cresol	-		-		Not readily

12.3 Bioaccumulative potential



SDS #: 37062

Product/substance	LogKow	BCF	Potential
ydrocarbons, C15-C20, n- alkanes, isoalkanes, cyclics, < 0.03% aromatics	-	171	low
2,6-di-tert-butyl-p-cresol methanol	5.1 -0.77	1277 <10	high Iow

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.
Mobility in soil	: Given its physical and chemical characteristics, the product generally shows low soil mobility The product is insoluble and floats on water Loss by evaporation is limited

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %.

12.6 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods	
<u>Product</u>	
Methods of disposal :	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	Yes.
	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used The following Waste Codes are only suggestions: 13 01 10*
Packaging	
Methods of disposal	The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



	ADR/RID	ADN	IMDG	ICAO/IATA	
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.	
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,6-di-tert-butyl-p- cresol)	-	-	
14.3 Transport hazard class(es)	-	9	-	-	
14.4 Packing group	-	-	-	-	
14.5 Environmental hazards	No.	Yes.	No.	No.	
Additional informat	ion				
ADN 14.6 Special precaut user	vessels. tions for : Transpor	uct is only regulated as a c t within user's premises d secure. Ensure that per	always transport in	closed containers that are	
user upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.					
14.7 Maritime trans bulk according to IN instruments		ble.			
SECTION 15: F	Regulatory infor	mation			
15.1 Safety, health a	nd environmental reg	ulations/legislation spec	cific for the substan	ce or mixture	
	No 1907/2006 (REAC	<u>) (H)</u>			
EU Regulation (EC	<u> </u>				
EU Regulation (EC	of substances subject	to authorization			
EU Regulation (EC		to authorization			
EU Regulation (EC Annex XIV - List o Annex XIV		to authorization			
EU Regulation (EC Annex XIV - List of Annex XIV None of the comp	of substances subject	<u>to authorization</u>			

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Are note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work



Industrial emissions (integrated pollution prevention and control) - Air	: Not listed	
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed	
Ozone depleting substance Not listed.	<u>es (1005/2009/EU)</u>	
Prior Informed Consent (Pl Not listed.	<u>C) (649/2012/EU)</u>	
Persistent Organic Polluta Not listed.	<u>nts</u>	
<u>Seveso Directive</u> This product is not controllec <u>National regulations</u>	I under the Seveso Directive.	
Social Security Code, Articles L 461-1 to L 461-7	 Fydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics methanol Mineral oil Synthetic oil 	RG 36, RG 36bis, RG 84 RG 84 RG36 RG36
Reinforced medical surveillance	: Decree n ° 2012-135 of January 30, 2012 relating occupational medicine: not applicable	to the organization of
Other regulations	 Art R4412-1 to R4412-57 of the Labor Code relating dangerous chemical agents. Art R.4624-22 to R.4624-28 of the Labor Code relation Monitoring of the state of health of workers. 	

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals Not listed.

LU - Luxembourg prohibited chemicals in the workplace



Not listed.

Inventory list	
Australia inventory (AIIC)	: All components are listed or exempted.
Canada inventory (DSL/NDSL)	: All components are listed or exempted.
China inventory (IECSC)	: All components are listed or exempted.
Europe inventory (EC)	: 🕅 components are listed or exempted.
Japan inventory	 Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC)	: All components are listed or exempted.
Philippines inventory (PICCS)	: All components are listed or exempted.
Korea inventory (KECI)	: All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	: All components are listed or exempted.
Thailand inventory	: Not determined.
Turkey inventory	: Not determined.
United States inventory (TSCA 8b)	: All components are listed or exempted.
Vietnam inventory	: Not determined.
The information stated in this section relates so	aly to the conformity of the chemical product with the

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical Safety	: See exposure scenarios
Assessment	

SECTION 16: Other information

Indicates information that has changed from previously issued version.

	0 1 5
Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DNEL = Derived No Effect Level
	DMEL = Derived Minimal Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	vPvB = Very Persistent and Very Bioaccumulative
	PNEC = Predicted No Effect Concentration
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	OEL = Occupational Exposure Limit
	VOC = Volatile Organic Compound
	UVCB Substance of unknown or Variable composition, Complex reaction products
	or Biological material
	NOEC No Observed Effect Concentration
	QSAR = Quantitative Structure–Activity Relationship

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Rquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

Revision:2022/10/28	Version : 2	France	ENGLISH	16/23
---------------------	-------------	--------	---------	-------



H225Highly flammable liquid and vapor.H301Toxic if swallowed.H304May be fatal if swallowed and enters airways.H311Toxic in contact with skin.H331Toxic if inhaled.H370Causes damage to organs.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.H412AQUATIC HAZARD (ACUTE) - Category 3Aquatic Acute 1AQUATIC HAZARD (ACUTE) - Category 1Aquatic Chronic 1AQUATIC HAZARD (LONG-TERM) - Category 1Aquatic Chronic 3AQUATIC HAZARD (LONG-TERM) - Category 3Asp. Tox. 1FLAMMABLE LIQUIDS - Category 1Flam. Liq. 2FLAMMABLE LIQUIDS - Category 2STOT SE 1SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -		
H304May be fatal if swallowed and enters airways.H311Toxic in contact with skin.H331Toxic if inhaled.H370Causes damage to organs.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Full text of classifications [CLP/GHS]Image: Acute 1Acute Tox. 3Aquatic Acute 1Acute ToXICITY - Category 3Aquatic Chronic 1AQUATIC HAZARD (ACUTE) - Category 1Aquatic Chronic 3AQUATIC HAZARD (LONG-TERM) - Category 3Asp. Tox. 1ASPIRATION HAZARD - Category 1Flam. Liq. 2FLAMMABLE LIQUIDS - Category 2	H225	Highly flammable liquid and vapor.
H311Toxic in contact with skin.H331Toxic if inhaled.H370Causes damage to organs.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Full text of classifications [CLP/GHS]Image: Acute 1 aquatic Chronic 1 aquatic Chronic 3 aquatic Chronic 3 asp. Tox. 1 Flam. Liq. 2Aguatic Acute 1Aguatic Chronic 3Asp. Tox. 1Flam. Liq. 2Flam. Liq. 2	H301	Toxic if swallowed.
H331 H370 H400 H410 H412Toxic if inhaled. Causes damage to organs. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.Full text of classifications [CLP/GHS]ACUTE TOXICITY - Category 3 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 3 Asp. Tox. 1 Flam. Liq. 2ACUTE TOXICITY - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 2	H304	May be fatal if swallowed and enters airways.
H370 H400Causes damage to organs. Very toxic to aquatic life. Very toxic to aquatic life. H412H410 H412Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.Full text of classifications [CLP/GHS]ACUTE TOXICITY - Category 3 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 3 Asp. Tox. 1 Flam. Liq. 2ACUTE TOXICITY - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 2	H311	Toxic in contact with skin.
H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects. Full text of classifications [CLP/GHS]Acute Tox. 3 Aquatic Acute 1ACUTE TOXICITY - Category 3Aquatic Chronic 1AQUATIC HAZARD (ACUTE) - Category 1Aquatic Chronic 3AQUATIC HAZARD (LONG-TERM) - Category 1Aquatic Chronic 3AQUATIC HAZARD (LONG-TERM) - Category 3Asp. Tox. 1ASPIRATION HAZARD - Category 1Flam. Liq. 2FLAMMABLE LIQUIDS - Category 2	H331	Toxic if inhaled.
H410 H412Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.Full text of classifications [CLP/GHS]Kcute Tox. 3 Aquatic Acute 1ACUTE TOXICITY - Category 3 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3 Asp. Tox. 1 Flam. Liq. 2H410 H412Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.	H370	Causes damage to organs.
H412Harmful to aquatic life with long lasting effects.Full text of classifications [CLP/GHS]Image: Colspan="2">Koute Tox. 3Aquatic Acute 1ACUTE TOXICITY - Category 3Aquatic Chronic 1AQUATIC HAZARD (ACUTE) - Category 1Aquatic Chronic 3AQUATIC HAZARD (LONG-TERM) - Category 1Aquatic Chronic 3AQUATIC HAZARD (LONG-TERM) - Category 3Asp. Tox. 1ASPIRATION HAZARD - Category 1Flam. Liq. 2FLAMMABLE LIQUIDS - Category 2	H400	Very toxic to aquatic life.
Full text of classifications [CLP/GHS] Acute Tox. 3 ACUTE TOXICITY - Category 3 Aquatic Acute 1 AQUATIC HAZARD (ACUTE) - Category 1 Aquatic Chronic 1 AQUATIC HAZARD (LONG-TERM) - Category 1 Aquatic Chronic 3 AQUATIC HAZARD (LONG-TERM) - Category 3 Asp. Tox. 1 ASPIRATION HAZARD - Category 1 Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2	H410	Very toxic to aquatic life with long lasting effects.
Kette Tox. 3ACUTE TOXICITY - Category 3Aquatic Acute 1AQUATIC HAZARD (ACUTE) - Category 1Aquatic Chronic 1AQUATIC HAZARD (LONG-TERM) - Category 1Aquatic Chronic 3AQUATIC HAZARD (LONG-TERM) - Category 3Asp. Tox. 1ASPIRATION HAZARD - Category 1Flam. Liq. 2FLAMMABLE LIQUIDS - Category 2	H412	Harmful to aquatic life with long lasting effects.
Aquatic Acute 1AQUATIC HAZARD (ACUTE) - Category 1Aquatic Chronic 1AQUATIC HAZARD (LONG-TERM) - Category 1Aquatic Chronic 3AQUATIC HAZARD (LONG-TERM) - Category 3Asp. Tox. 1ASPIRATION HAZARD - Category 1Flam. Liq. 2FLAMMABLE LIQUIDS - Category 2	Full text of classifications [CLP/GHS]	
Aquatic Acute 1AQUATIC HAZARD (ACUTE) - Category 1Aquatic Chronic 1AQUATIC HAZARD (LONG-TERM) - Category 1Aquatic Chronic 3AQUATIC HAZARD (LONG-TERM) - Category 3Asp. Tox. 1ASPIRATION HAZARD - Category 1Flam. Liq. 2FLAMMABLE LIQUIDS - Category 2	Acute Tox. 3	ACUTE TOXICITY - Category 3
Aquatic Chronic 1AQUATIC HAZARD (LONG-TERM) - Category 1Aquatic Chronic 3AQUATIC HAZARD (LONG-TERM) - Category 3Asp. Tox. 1ASPIRATION HAZARD - Category 1Flam. Liq. 2FLAMMABLE LIQUIDS - Category 2	Aquatic Acute 1	
Asp. Tox. 1 ASPIRATION HAZARD - Category 1 Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2	Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2	Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
	Asp. Tox. 1	ASPIRATION HAZARD - Category 1
STOT SE 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -	Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
	STOT SE 1	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 1

Additionnal details on the supplier of the product

rotalEnergies Marketing Caraïbes ZI. Californie 97232 Le Lamentin Martinique France Tel : +596 596 504 957		
TotalEnergies Marketing Mayotte Immeuble Jacaranda 1, Lotissement Les 3 vallées Majicavo Lamir BP 867 kawéni 97600 MAMOUDZOU tél : +262 (0) 269 60 12 94 fax : +262 (0) 269 60 17 30		
✓otalEnergies Marketing Ré 3 rue Jacques Prévert BP286 – 97827 LE PORT tél : +262 (0) 262 55 20 20 fax : +262 (0) 262 55 20 31	union	
)ate of revision	· 2022/10/28	

•	2022/10/20
:	2021/04/21
:	2
	:

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex to the extended Safety Data Sheet (eSDS)

Identification of the substance or mixture **Product definition** : Mixture : 37062 Code : AZOLLA AL 32 **Product name** Section 1 - Title Short title of the exposure : Formulation additives, lubricants and greases - Industrial scenario List of use descriptors : Identified use name: Formulation additives, lubricants and greases - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15 Sector of end use: SU03, SU10 Subsequent service life relevant for that use: No. Environmental Release Category: ERC02 **Environmental contributing** : scenarios **Health Contributing** 2 scenarios **Processes and activities** : Industrial formulation of lubricant additives, lubricants and greases. Includes material transfers, mixing, large and small scale packing, sampling, maintenance. covered by the exposure scenario

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:		
ATIEL-ATC SPERC 2.Ai-I.v1		
Amounts used	÷	Volume manufactured/imported (tonnes/year) : 1.00E+04
		Fraction of EU tonnage used in region : 0.1 Fraction of regional tonnage used locally : 0.1
Frequency and duration of use	:	Emission days (days per year) : 300
Environment factors not	:	Local freshwater dilution factor : 10
influenced by risk management		Local marine water dilution factor : 100
Other conditions affecting environmental exposure	:	Negligible wastewater emissions as process operates without water contact.
		Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.00E-05 Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-12
		Release fraction to soil from process (after typical onsite RMMs): 0
Technical conditions and measures at process level (source) to prevent release	:	Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to	:	Treat air emission to provide a typical removal efficiency of (%) : 70
reduce or limit discharges, air emissions and releases to soil		Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.
Organizational measures to prevent/limit release from site	:	Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
1		

AZOLLA AL 32	- Formulation additives, lubricants and greases Industrial
Conditions and measures related to sewage treatment plant	 Estimated substance removal from wastewater via domestic sewage treatment (%): (%): 69 Assumed domestic sewage treatment plant flow (m³/d): 2.00E+03 Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal (kg/day): 1 154 460
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.
Contributing scenario controlling worker exposure for 2: No exposure assessment presented for human health. Conditions and measures related to personal protection, hygiene and health evaluation	

Section 3 - Exposure estimation and reference to its source

Website:	:	Not applicable.	
Exposure estimation and reference to its source - Environment: 1:			
Exposure assessment (environment):	:	Used ECETOC TRA model.	
Exposure estimation and reference to its source	1	Not available.	
Exposure estimation and reference to its source - Workers: 2:			
Exposure assessment (human):	:	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.	
Exposure estimation and reference to its source	;	Not available.	

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Product definition : Mixture : 37062 Code : AZOLLA AL 32 **Product name** Section 1 - Title Short title of the exposure : General use of lubricants and greases in vehicles or machinery - Industrial scenario List of use descriptors : Identified use name: General use of lubricants and greases in vehicles or machinery - Industrial Process Category: PROC01, PROC02, PROC08b, PROC09 Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC04, ERC07 **Environmental contributing** : scenarios **Health Contributing** 2 scenarios **Processes and activities** : Covers general use of lubricants and greases in vehiculs or machinery in closed systems. Includes filling and draining of containers and operation of enclosed covered by the exposure machinery (including engines) and associated maintenance and storage activities. scenario

Section 2 - Exposure controls

Contributing scenario contro	lliı	ng environmental exposure for 1:	
ATIEL-ATC SPERC 4.Bi.v1			
Amounts used	1	Volume manufactured/imported (tonnes/year) : 2.63E+03	
		Fraction of EU tonnage used in region : 0.1 Fraction of regional tonnage used locally : 0.1	
Frequency and duration of use	:	Emission days (days per year) : 300	
Environment factors not influenced by risk management	:	Local freshwater dilution factor : 10 Local marine water dilution factor : 100	
Other conditions affecting environmental exposure	:	Negligible wastewater emissions as process operates without water contact. Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.00E-05 Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-12 Release fraction to soil from process (after typical onsite RMMs): 0	
Technical conditions and measures at process level (source) to prevent release	:	Common practices vary across sites thus conservative process release estimates used.	
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	:	Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.	
Organizational measures to prevent/limit release from site	:	Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.	

AZOLLA AL 32	General use of lubricants and greases in vehicles or machinery - Industrial
Conditions and measures related to sewage treatment plant	 Estimated substance removal from wastewater via domestic sewage treatment (%): (%): 69 Assumed domestic sewage treatment plant flow (m³/d): 2.00E+03 Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal (kg/day): 303 760
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.
Contributing scenario contro No exposure assessment pre Conditions and measures re	-

Section 3 - Exposure estimation and reference to its source

Website:	Not applicable.			
Exposure estimation and ref	Exposure estimation and reference to its source - Environment: 1:			
Exposure assessment (environment):	Used ECETOC TRA model.			
Exposure estimation and reference to its source	Not available.			
Exposure estimation and reference to its source - Workers: 2:				
Exposure assessment (human):	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.			
Exposure estimation and reference to its source	Not available.			

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture			
Product definition	: Mixture		
Code	: 37062		
Product name	: AZOLLA AL 32		
Section 1 - Title			
Short title of the exposure scenario	: General use of lubricants and greases in vehicles or machinery - Professional		
List of use descriptors	 Identified use name: General use of lubricants and greases in vehicles or machinery - Professional Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20 Sector of end use: SU22 Subsequent service life relevant for that use: No. Environmental Release Category: ERC09a, ERC09b 		
Environmental contributing scenarios	:		
Health Contributing scenarios	:		
Processes and activities covered by the exposure scenario	: Covers general use of lubricants and greases in vehiculs or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.		

Section 2 - Exposure controls

Contributing sconario contro	ш.	a anvironmental expecture for 1:	
Contributing scenario controlling environmental exposure for 1:			
ATIEL-ATC SPERC 9.Bp.v1			
Amounts used	÷	Volume manufactured/imported (tonnes/year) : 5.39E+03	
		Fraction of EU tonnage used in region : 0.1	
		Fraction of regional tonnage used locally : 0.1	
Frequency and duration of use	:	Emission days (days per year) : 365	
Environment factors not	:	Local freshwater dilution factor : 10	
influenced by risk management		Local marine water dilution factor : 100	
Other conditions affecting environmental exposure	:	Negligible wastewater emissions as process operates without water contact.	
		Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 1.00E-04	
		Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-04	
		Release fraction to soil from process (after typical onsite RMMs): 1.00E-03	
Technical conditions and measures at process level (source) to prevent release	:	Common practices vary across sites thus conservative process release estimates used.	
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	:	Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Organizational measures to prevent/limit release from site	•	Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.	
I			

AZOLLA AL 32	General use of lubricants and greases in vehicles or machinery - Professional
Conditions and measures related to sewage treatment plant	 Estimated substance removal from wastewater via domestic sewage treatment (%): (%): 69 Assumed domestic sewage treatment plant flow (m³/d): 2.00E+03 Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal (kg/day): 764
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.
Contributing scenario contro No exposure assessment pre Conditions and measures re	

Section 3 - Exposure estimation and reference to its source

Website:	Not applicable.			
Exposure estimation and ref	Exposure estimation and reference to its source - Environment: 1:			
Exposure assessment (environment):	Used ECETOC TRA model.			
Exposure estimation and reference to its source	Not available.			
Exposure estimation and reference to its source - Workers: 2:				
Exposure assessment (human):	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.			
Exposure estimation and reference to its source	Not available.			

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.