

# TRAXIUM DUAL 9 FE 75W-90

Transmission Oil

## KEY DATA

**HIGH PERFORMANCE SYNTHETIC OIL FOR GEARS**

**SAE 75W-90**

**FUEL ECONOMY**

## INTERNATIONAL STANDARDS

- API GL-4
- API GL-5
- API MT-1
- SAE J2360
- MIL-PRF 2105 E and MIL-L 2105 D

## MANUFACTURER APPROVALS<sup>1</sup>

- MB-Approval 235.8
- MAN 341 type Z-2
- MAN 342 type S-1
- SCANIA STO 1:0 (meet the requirement of)
- SCANIA STO 1:1 G
- SCANIA STO 2:0 A FS
- VOLVO 97312 / MACK GO-J Plus
- ZF TE-ML 02B, 05A, 12L, 12N, 16F, 17B, 19C, 21A
- MERITOR 076-N
- DAF
- IVECO RAS1



<sup>1</sup> Please refer to car owner's manual

## TECHNOLOGY

### Life-boost technology

**Your peace of mind solution.**

*Life-boost technology will maximize the durability of the components and parts of the driveline equipment of your vehicle.*

Our products will offer the best services as your vehicle will require drastically less maintenance providing reduced Total Cost Ownership (TCO) with on top a significant extended drain interval. **A solution which offer a peace of mind throughout the normal lifetime of your vehicle.**Life-Boost techno



## APPLICATIONS

TRAXIUM DUAL 9 FE 75W-90 is high performance synthetic oil developed for synchronized or non- synchronized manual gearboxes, axles and reduction gears requiring API GL-4, GL-5, MT-1 or MIL-PRF-2105E and MIL-L 2105 D.

TRAXIUM DUAL 9 FE 75W-90 is a synthetic lubricant of extremely high performance developed based on the T.D.L. (Drive Line Total) concept which is suitable for manual gearboxes and axles subjected to severe conditions of use.

TRAXIUM DUAL 9 FE 75W-90 suits particularly the lubrication of the gears hypoid and axles of most manufacturers such as Mack, MAN, DAF, IVECO, MERCEDES, VOLVO, RENAULT, MACK with extended drain intervals up.

## CUSTOMERS BENEFITS

- Reduced fuel consumption in comparison with standard lubricants due to TOTAL's Fuel Economy technology.
- Reduced cost of maintenance: specially formulated to reach extended drain intervals recommended by the manufacturer.
- Suitable for multi-brand fleet customers: this lubricant adapted for gearboxes and axles of several OEM, thus enabling customers to use this lubricant for the whole fleet.
- Excellent protection of axles and manual gearboxes against wear and corrosion due to extreme-pressure properties of oil.
- Improved driver start up experience: low temperature fluidity due to a high viscosity index, generating benefits during cold starts and limiting drag losses and fuel consumption.
- Excellent stability in operation due to high viscosity index.
- High compatibility with oil filters due to antifoam properties.
- Supports rationalisation of products (MERCEDES BENZ, MAN, VOLVO, etc).

## CHARACTERISTICS<sup>2</sup>

| TEST                          | UNIT               | TEST METHOD | RESULT |
|-------------------------------|--------------------|-------------|--------|
| Viscosity grade               | -                  | -           | 75W-90 |
| Kinematic viscosity at 40°C   | mm <sup>2</sup> /s | ASTM D445   | 101    |
| Kinematic viscosity at 100°C  | mm <sup>2</sup> /s | ASTM D445   | 15     |
| Viscosity Index               | -                  | ASTM D2270  | 157    |
| Flashpoint                    | °C                 | ASTM D92    | 190    |
| Pour point                    | °C                 | ASTM D97    | -51    |
| Density                       | Kg/m <sup>3</sup>  | DIN 51757 D | 866    |
| Viscosity Brookfield at -40°C | mm <sup>2</sup> /s | -           | 66 000 |

<sup>2</sup> The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

## RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations. The product should not be stored at temperatures over 60°C.

It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet.

This can be obtained on request from your local reseller and is available for consultation at <http://sdstotalms.total.com>.

This product should not be used for any purposes other than the ones for which it is intended.

TOTAL LUBRIFIANTS – Immeuble Spazio  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

TRAXIUM DUAL 9 FE 75W-90  
Last update of this datasheet: 09/2021

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at [www.lubricants.total.com](http://www.lubricants.total.com).