

ALTIS SH 2

SDS # : 30400

Date of previous revision : 2022/02/11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : ALTIS SH 2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
<input checked="" type="checkbox"/> Lubricating grease Use of lubricants and greases in open systems - Professional Formulation additives, lubricants and greases - Industrial General use of lubricants and greases in vehicles or machinery - Industrial General use of lubricants and greases in vehicles or machinery - Professional Use of lubricants and greases in open systems - Industrial

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants
562 Avenue du Parc de L'île
92029 Nanterre Cedex FRANCE
Tél: +33 (0)1 41 35 40 00
Fax: +33 (0)1 41 35 84 71
rm.msds-lubs@totalenergies.com

See section 16 to have the contact details of the local supplier

Contact

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59
In France - Poison centers:
ANGERS : 02 41 48 21 21
BORDEAUX : 05 56 96 40 80
LILLE : 08 00 59 59 59
LYON : 04 72 11 69 11
MARSEILLE : 04 91 75 25 25
NANCY : 03 83 22 50 50
PARIS : 01 40 05 48 48
STRASBOURG : 03 88 37 37 37
TOULOUSE : 05 61 77 74 47

Supplier

Telephone number : Emergency phone: +44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P273 - Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Not available.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1$ %.


Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture


Product/substance	Identifiers	% (w/w)	Classification	Specific Conc. Limits, M-factors and ATEs	Type
A mixture of: 3,3'-dicyclohexyl-1,1'-methylenebis (4,1-phenylene)diurea; 3-cyclohexyl-1-(4-(4-(3-octadecylureido)benzyl)phenyl)urea; 3,3'-dioctadecyl-1,1'-methylenebis (4,1-phenylene)diurea	REACH #: 01-0000015606-69 EC: 406-530-2	≤ 10	Aquatic Chronic 4, H413	-	[1]
4,4'-methylene bis	EC: 233-593-1	≤ 3	Aquatic Chronic 4,	-	[1]

(dibutylidithiocarbamate)	CAS: 10254-57-6		H413		
O,O,O-tris(2(or 4)-C9-10-isoalkylphenyl) phosphorothioate	REACH #: 01-0000015643-71 EC: 406-940-1 CAS: 126019-82-7 Index: 015-171-00-7	≤3	Aquatic Chronic 2, H411	-	[1]
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	REACH #: 01-2119491299-23 EC: 270-128-1 CAS: 68411-46-1	≤1	Repr. 2, H361f	-	[1]
4-nonylphenol, branched	EC: 284-325-5 CAS: 84852-15-3 Index: 601-053-00-8	≤0.1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Repr. 2, H361fd Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 1300 mg/kg M [Acute] = 10 M [Chronic] = 10	[1] [2]

Additional information :  Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346 The product is made from synthetic base oils

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type



 Substance classified with a health or environmental hazard

[2] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** :  Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** :  Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders : ☒ No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : ☒ Adverse symptoms may include the following:
irritation
dryness
cracking
Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.
Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : ☒ In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products : ☒ carbon monoxide
carbon dioxide
nitrogen oxides
phosphorus oxides
sulfur oxides
Hydrogen sulfide
Mercaptans

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : ☒ No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

- Small spill** : ☒ Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : ☒ Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Protective measures** : ☒ Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Reportable hazardous constituent(s) contained in UVCB and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Advisory OEL : ☒ Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

DNELs/DMELs

Product/substance	Type	Exposure	Value	Population	Effects
O,O,O-tris(2(or 4)-C9-10-isoalkylphenyl) phosphorothioate	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	16 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	2.89 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	11.75 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	33.3 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	0.04 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.04 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.08 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.14 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	0.6 mg/m ³	Workers	Systemic
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	DNEL	Long term Oral	0.08 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.4 mg/kg bw/day	General population	Systemic
4-nonylphenol, branched	DNEL	Long term Oral	0.08 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.4 mg/kg bw/day	General population	Systemic

	DNEL	Long term Inhalation	0.4 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	0.5 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	0.8 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	1 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	3.8 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	7.5 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	7.6 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	15 mg/kg bw/day	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Name	Method Detail
A mixture of: 3,3'-dicyclohexyl-1,1'-methylenebis(4,1-phenylene)diurea; 3-cyclohexyl-1-(4-(4-(3-octadecylureido)benzyl)phenyl)urea; 3,3'-dioctadecyl-1,1'-methylenebis(4,1-phenylene)diurea	Fresh water	0.001 mg/l	-
	Marine water	0.0001 mg/l	-
	Fresh water sediment	2.8 mg/kg dwt	-
	Marine water sediment	0.28 mg/kg dwt	-
	Soil	0.56 mg/kg dwt	-
	Sewage Treatment Plant	1 mg/l	-
O,O,O-tris(2(or 4)-C9-10-isoalkylphenyl)phosphorothioate	Soil	20 mg/kg dwt	-
	Fresh water sediment	100 µg/kg dwt	-
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Marine water sediment	10 µg/kg dwt	-
	Fresh water	33.8 µg/l	-
	Marine water	3.38 µg/l	-
	Fresh water sediment	446 µg/kg dwt	-
	Marine water sediment	44.6 µg/kg dwt	-
	Soil	1.76 mg/kg dwt	-

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. EN 166

Skin protection

Hand protection	<p>: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.</p> <p><input checked="" type="checkbox"/> Hydrocarbon-proof gloves nitrile rubber Fluorinated rubber</p> <p>Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.</p> <p>In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency</p>
Body protection	<p>: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</p>
Other skin protection	<p>: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</p>
Respiratory protection	<p>: Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces. In case of inadequate ventilation wear respiratory protection: Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.</p>
Environmental exposure controls	<p>: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.</p>

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: <input checked="" type="checkbox"/> Liquid. [grease]	
Color	: light yellow	
Odor	: Characteristic.	
Odor threshold	: Not available.	
pH	: Not applicable.	<input checked="" type="checkbox"/> Product is non-soluble (in water).
Melting point/freezing point	: <input checked="" type="checkbox"/> 240°C [ISO 3016]	
Initial boiling point and boiling range	: <input checked="" type="checkbox"/> Not applicable.	
Flash point	: Not applicable.	
Evaporation rate	: Not available.	
Flammability	: <input checked="" type="checkbox"/> Not applicable.	

Lower and upper explosion limit : ☒ Not available.
Vapor pressure : ☒ Not applicable.
Vapor density : ☒ Not available.
Relative density : ☒ 0.9 [ISO 12185]
Density : ☒ 0.9 g/cm³ [20°C] [ISO 12185]
Solubility(ies) :

Media	Result
<input checked="" type="checkbox"/> Water	Not soluble

Miscible with water : No.
Partition coefficient: n-octanol/ water : Not applicable.
Auto-ignition temperature : Not applicable.
Decomposition temperature : ☒ 240°C
Viscosity : ☒ Not applicable.
Particle characteristics
Median particle size : ☒ Not applicable.

9.2 Other information

No other relevant physical and chemical parameters for the safe use of the product

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid : ☒ Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking.
10.5 Incompatible materials : ☒ Strong oxidizing agents
10.6 Hazardous decomposition products : ☒ carbon monoxide
 carbon dioxide
 nitrogen oxides
 phosphorus oxides
 sulfur oxides
 Hydrogen sulfide
 Mercaptans

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
<div> <div></div> mixture of: 3,3'-dicyclohexyl-1,1'-methylenebis(4,1-phenylene)diurea; 3-cyclohexyl-1-(4-(4-(3-octadecylureido)benzyl)phenyl)urea; 3,3'-dioctadecyl-1,1'-methylenebis(4,1-phenylene)diurea </div>	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	-
4,4'-methylene bis (dibutyldithiocarbamate)	LC50 Inhalation Vapor	Rat	80.4 mg/l	1 hours	-
	LC50 Inhalation Vapor	Rat	20.1 mg/l	4 hours	-
	LD50 Dermal	Rabbit	2000 mg/kg	-	-
O,O,O-tris(2(or 4)-C9-10-isoalkylphenyl)phosphorothioate	LD50 Oral	Rat	16000 mg/kg	-	-
	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	-
	LC50 Inhalation Vapor	Rat	80.4 mg/l	1 hours	-
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 4-nonylphenol, branched	LC50 Inhalation Vapor	Rat	20.1 mg/l	4 hours	-
	LD50 Dermal	Rat	>2000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>2000 mg/kg	-	OECD 401
	LD50 Oral	Rat	>5000 mg/kg	-	-
	LD50 Oral	Rat	1300 mg/kg	-	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/substance	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
<div> <div></div> mixture of: 3,3'-dicyclohexyl-1,1'-methylenebis(4,1-phenylene)diurea; 3-cyclohexyl-1-(4-(4-(3-octadecylureido)benzyl)phenyl)urea; 3,3'-dioctadecyl-1,1'-methylenebis(4,1-phenylene)diurea </div>	N/A	N/A	N/A	20.1	5.1
4,4'-methylene bis(dibutyldithiocarbamate)	16000	N/A	N/A	N/A	N/A
O,O,O-tris(2(or 4)-C9-10-isoalkylphenyl)phosphorothioate	N/A	N/A	N/A	20.1	5.1
4-nonylphenol, branched	1300	N/A	N/A	N/A	N/A

Irritation/Corrosion

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Sensitization

Conclusion/Summary :

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Conclusion/Summary : Based on available data, the classification criteria are not met.

Aspiration hazard

Conclusion/Summary : Based on available data, the classification criteria are not met.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : Defatting to the skin. May cause skin dryness and irritation.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
irritation
dryness
cracking
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.
General : No known significant effects or critical hazards.
Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.


11.2 Information on other hazards

11.2.1 Endocrine disrupting properties


This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information

SECTION 12: Ecological information

 Harmful to aquatic life with long lasting effects.

12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
 mixture of: 3,3'-dicyclohexyl-1,1'-methylenebis(4,1-phenylene) diurea; 3-cyclohexyl-1-(4-(4-(3-octadecylureido)benzyl)phenyl)urea; 3,3'-dioctadecyl-1,1'-methylenebis(4,1-phenylene)diurea 4,4'-methylene bis (dibutylthiocarbamate) O,O,O-tris(2(or 4)-C9-10-isoalkylphenyl) phosphorothioate 4-nonylphenol, branched	Acute EC50 100 mg/l	Micro-organism	3 hours	-
	Acute EC50 1000 mg/l	Micro-organism	3 hours	-
	Acute EC50 >100 mg/l	Algae	72 hours	OECD 201
	Acute EC50 >100 mg/l	Micro-organism	3 hours	OECD 209
	Acute LC50 >25 mg/l	Fish	96 hours	-
	Chronic NOEC ≥10 mg/l	Daphnia - Daphnia magna	21 days	OECD 202
	Acute EC50 0.03 mg/l	Algae - Skeletonema costatum	72 hours	-
	Marine water	Algae - Skeletonema costatum	96 hours	-
	Acute EC50 0.027 mg/l	Crustaceans - Moina macrocopa	48 hours	OECD
	Marine water	Fish - Pleuronectes americanus - Larvae	96 hours	-
	Acute EC50 0.044 mg/l	Algae - Skeletonema costatum	96 hours	-
	Acute LC50 17 µg/l Marine water	Crustaceans - Gammarus fossarum - Adult	21 days	-
	Chronic EC10 0.012 mg/l Marine water	Fish - Pimephales promelas - Embryo	33 days	-
	Chronic NOEC 5 µg/l Fresh water			
	Chronic NOEC 7.4 µg/l Fresh water			

12.2 Persistence and degradability

Conclusion/Summary : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
A mixture of: 3,3'-dicyclohexyl-1,1'-methylenebis(4,1-phenylene) diurea; 3-cyclohexyl-1-(4-(4-(3-octadecylureido)benzyl)phenyl)urea; 3,3'-dioctadecyl-1,1'-methylenebis(4,1-phenylene) diurea O,O,O-tris(2(or 4)-C9-10-isoalkylphenyl) phosphorothioate Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	-	-	Not readily
	-	-	Not readily
	-	-	Not readily

12.3 Bioaccumulative potential

Product/substance	LogK _{ow}	BCF	Potential
4,4'-methylene bis (dibutylthiocarbamate)	8.42	10.86	low
O,O,O-tris(2(or 4)-C9-10-isoalkylphenyl) phosphorothioate	20	48	low
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	5.1	1730	high
4-nonylphenol, branched	5.4	740	high

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

Mobility in soil : Given its physical and chemical characteristics, the product has no soil mobility.
The product is insoluble and floats on water. Loss by evaporation is limited.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1$ %.

12.6 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 12 01 12*

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	9005	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., MOLTEN (O, O,O-tris(2(or 4)-C9-10-isoalkylphenyl) phosphorothioate, 4-nonylphenol, branched)	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADN : The product is only regulated as a dangerous good when transported in tank vessels.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
4-nonylphenol, branched and linear substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof	Endocrine disrupting properties for environment	Candidate	ED/169/2012	12/19/2012

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Reinforced medical surveillance

Mineral oil
Synthetic oil

RG36
RG36

: Decree n ° 2012-135 of January 30, 2012 relating to the organization of occupational medicine: not applicable

Art R4412-1 to R4412-57 of the Labor Code relating to the provisions applicable to dangerous chemical agents.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

LU - Luxembourg prohibited chemicals in the workplace

Not listed.

Inventory list

Australia inventory (AIIC)	: Not determined.
Canada inventory (DSL/NDL)	: Not determined.
China inventory (IECSC)	: All components are listed or exempted.
Europe inventory (EC)	: All components are listed or exempted.
Japan inventory	: Japan inventory (CSCL) : At least one component is not listed. Japan inventory (ISHL) : Not determined.
New Zealand Inventory of Chemicals (NZIoC)	: Not determined.
Philippines inventory (PICCS)	: Not determined.
Korea inventory (KECI)	: Not determined.
Taiwan Chemical Substances Inventory (TCSI)	: Not determined.
Thailand inventory	: Not determined.
Turkey inventory	: Not determined.
United States inventory (TSCA 8b)	: Not determined.
Vietnam inventory	: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical Safety Assessment

: See exposure scenarios

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DNEL = Derived No Effect Level
 DMEL = Derived Minimal Effect Level
 EUH statement = CLP-specific Hazard statement
 N/A = Not available
 PBT = Persistent, Bioaccumulative and Toxic
 vPvB = Very Persistent and Very Bioaccumulative
 PNEC = Predicted No Effect Concentration
 LC50 = Median lethal concentration
 LD50 = Median lethal dose
 OEL = Occupational Exposure Limit
 VOC = Volatile Organic Compound
 UVCB Substance of unknown or Variable composition, Complex reaction products or Biological material
 NOEC No Observed Effect Concentration
 QSAR = Quantitative Structure–Activity Relationship

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H302 H314 H318 H361f H361fd H400 H410 H411 H412 H413	Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage. Suspected of damaging fertility. Suspected of damaging fertility. Suspected of damaging the unborn child. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life.
---	--

Full text of classifications [CLP/GHS]

Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Aquatic Chronic 3 Aquatic Chronic 4 Eye Dam. 1 Repr. 2 Skin Corr. 1B	ACUTE TOXICITY - Category 4 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 3 AQUATIC HAZARD (LONG-TERM) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 TOXIC TO REPRODUCTION - Category 2 SKIN CORROSION/IRRITATION - Category 1B
---	--

Additional details on the supplier of the product



TotalEnergies

ALTIS SH 2

SDS # : 30400

TotalEnergies Marketing Caraïbes
ZI. Californie
97232 Le Lamentin
Martinique France
Tel : +596 596 504 957

TotalEnergies Marketing Mayotte
Immeuble Jacaranda 1, Lotissement Les 3 vallées Majicavo Lamir
BP 867 kawéni
97600 MAMOUDZOU
tél : +262 (0) 269 60 12 94
fax : +262 (0) 269 60 17 30

TotalEnergies Marketing Réunion
3 rue Jacques Prévert
BP286 – 97827 LE PORT
tél : +262 (0) 262 55 20 20
fax : +262 (0) 262 55 20 31

Date of revision : 2022/10/24

Date of previous revision : 2022/02/11

Version : 2

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 30400
Product name : ALTIS SH 2

Section 1 - Title

Short title of the exposure scenario : Use of lubricants and greases in open systems - Industrial
List of use descriptors : **Identified use name:** Use of lubricants and greases in open systems - Industrial
Process Category: PROC01, PROC02, PROC07, PROC08b, PROC09, PROC10, PROC13
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC04
Environmental contributing scenarios :
Health Contributing scenarios :

Processes and activities covered by the exposure scenario : Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mold releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 4.Ci.v1
Amounts used : Volume manufactured/imported (tonnes/year) : 3.81E+02
Fraction of EU tonnage used in region : 0.1
Fraction of regional tonnage used locally : 0.1
Frequency and duration of use : Emission days (days per year) : 300
Environment factors not influenced by risk management : Local freshwater dilution factor : 10
Local marine water dilution factor : 100
Other conditions affecting environmental exposure : Negligible wastewater emissions as process operates without water contact.
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.0E-05
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 4.00E-11
Release fraction to soil from process (after typical onsite RMMs): 0
Technical conditions and measures at process level (source) to prevent release : Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil : Treat air emission to provide a typical removal efficiency of (%) : 70
Prevent discharge of undissolved substance to or recover from onsite wastewater.
User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.
Organizational measures to prevent/limit release from site : Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Date of issue/Date of revision : 4/6/2020

19/28

Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 69 Assumed domestic sewage treatment plant flow (m³/d) : 2.00E+03 Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/day) : 549 647
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation**Section 3 - Exposure estimation and reference to its source****Website:** : Not applicable.**Exposure estimation and reference to its source - Environment: 1:****Exposure assessment (environment):** : Used ECETOC TRA model.**Exposure estimation and reference to its source** : Not available.**Exposure estimation and reference to its source - Workers: 2:****Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.**Exposure estimation and reference to its source** : Not available.**Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES**

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 30400
Product name : ALTIS SH 2

Section 1 - Title

Short title of the exposure scenario : General use of lubricants and greases in vehicles or machinery - Industrial

List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or machinery - Industrial
Process Category: PROC01, PROC02, PROC08b, PROC09
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC04, ERC07

Environmental contributing scenarios :

Health Contributing scenarios :

Processes and activities covered by the exposure scenario	: Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.
---	---

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 4.Bi.v1

Amounts used	: Volume manufactured/imported (tonnes/year) : 2.63E+03 Fraction of EU tonnage used in region : 0.1 Fraction of regional tonnage used locally : 0.1
Frequency and duration of use	: Emission days (days per year) : 300
Environment factors not influenced by risk management	: Local freshwater dilution factor : 10 Local marine water dilution factor : 100
Other conditions affecting environmental exposure	: Negligible wastewater emissions as process operates without water contact. Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.00E-05 Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 4.00E-11 Release fraction to soil from process (after typical onsite RMMs): 0
Technical conditions and measures at process level (source) to prevent release	: Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	: Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.
Organizational measures to prevent/limit release from site	: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Date of issue/Date of revision : 4/3/2020

21/28

Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 69 Assumed domestic sewage treatment plant flow (m ³ /d) : 2.00E+03 Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/day) : 3 797 024
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation**Section 3 - Exposure estimation and reference to its source****Website:** : Not applicable.**Exposure estimation and reference to its source - Environment: 1:****Exposure assessment (environment):** : Used ECETOC TRA model.**Exposure estimation and reference to its source** : Not available.**Exposure estimation and reference to its source - Workers: 2:****Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.**Exposure estimation and reference to its source** : Not available.**Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES**

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition : Mixture
Code : 30400
Product name : ALTIS SH 2

Section 1 - Title

Short title of the exposure scenario : Use of lubricants and greases in open systems - Professional
List of use descriptors : **Identified use name:** Use of lubricants and greases in open systems - Professional
Process Category: PROC01, PROC02, PROC08a, PROC10, PROC11, PROC13
Sector of end use: SU22
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08a, ERC08d
Environmental contributing scenarios :
Health Contributing scenarios :

Processes and activities covered by the exposure scenario : Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mold releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 8.Cp.v1

Amounts used : Volume manufactured/imported (tonnes/year) : 2.24E+02
Fraction of EU tonnage used in region : 0.1
Fraction of regional tonnage used locally : 0.1
Frequency and duration of use : Emission days (days per year) : 365
Environment factors not influenced by risk management : Local freshwater dilution factor : 10
Local marine water dilution factor : 100
Other conditions affecting environmental exposure : Negligible wastewater emissions as process operates without water contact.
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 1.00E-04
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-04
Release fraction to soil from process (after typical onsite RMMs): 1.00E-03
Technical conditions and measures at process level (source) to prevent release : Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil : Prevent discharge of undissolved substance to or recover from onsite wastewater.
Organizational measures to prevent/limit release from site : Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 69 Assumed domestic sewage treatment plant flow (m ³ /d) : 2.00E+03 Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/day) : 3 508
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation**Section 3 - Exposure estimation and reference to its source****Website:** : Not applicable.**Exposure estimation and reference to its source - Environment: 1:****Exposure assessment (environment):** : Used ECETOC TRA model.**Exposure estimation and reference to its source** : Not available.**Exposure estimation and reference to its source - Workers: 2:****Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.**Exposure estimation and reference to its source** : Not available.**Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES**

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 30400
Product name : ALTIS SH 2

Section 1 - Title

Short title of the exposure scenario : Formulation additives, lubricants and greases - Industrial
List of use descriptors : **Identified use name:** Formulation additives, lubricants and greases - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Sector of end use: SU03, SU10
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02
Environmental contributing scenarios :
Health Contributing scenarios :

Processes and activities covered by the exposure scenario : Industrial formulation of lubricant additives, lubricants and greases. Includes material transfers, mixing, large and small scale packing, sampling, maintenance.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 2.Ai-I.v1

Amounts used : Volume manufactured/imported (tonnes/year) : 1.00E+04
Fraction of EU tonnage used in region : 0.1
Fraction of regional tonnage used locally : 0.1
Frequency and duration of use : Emission days (days per year) : 300
Environment factors not influenced by risk management : Local freshwater dilution factor : 10
Local marine water dilution factor : 100
Other conditions affecting environmental exposure : Negligible wastewater emissions as process operates without water contact.
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.00E-05
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 4.00E-11
Release fraction to soil from process (after typical onsite RMMs): 0
Technical conditions and measures at process level (source) to prevent release : Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil : Treat air emission to provide a typical removal efficiency of (%) : 70
Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.
Organizational measures to prevent/limit release from site : Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Date of issue/Date of revision : 4/3/2020

25/28

Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 69 Assumed domestic sewage treatment plant flow (m ³ /d) : 2.00E+03 Maximum allowable site tonnage (M _{safe}) based on release following total wastewater treatment removal (kg/day) : 14 430 773
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation**Section 3 - Exposure estimation and reference to its source**

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2:

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition : Mixture
Code : 30400
Product name : ALTIS SH 2

Section 1 - Title

Short title of the exposure scenario : General use of lubricants and greases in vehicles or machinery - Professional

List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or machinery - Professional
Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20
Sector of end use: SU22
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC09a, ERC09b

Environmental contributing scenarios :

Health Contributing scenarios :

Processes and activities covered by the exposure scenario	: Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.
---	---

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 9.Bp.v1

Amounts used	: Volume manufactured/imported (tonnes/year) : 5.39E+03 Fraction of EU tonnage used in region : 0.1 Fraction of regional tonnage used locally : 0.1
Frequency and duration of use	: Emission days (days per year) : 365
Environment factors not influenced by risk management	: Local freshwater dilution factor : 10 Local marine water dilution factor : 100
Other conditions affecting environmental exposure	: Negligible wastewater emissions as process operates without water contact. Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 1.00E-04 Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-04 Release fraction to soil from process (after typical onsite RMMs): 1.00E-03
Technical conditions and measures at process level (source) to prevent release	: Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	: Prevent discharge of undissolved substance to or recover from onsite wastewater.
Organizational measures to prevent/limit release from site	: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Date of issue/Date of revision : 4/6/2020

27/28

Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 69 Assumed domestic sewage treatment plant flow (m ³ /d) : 2.00E+03 Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/day) : 9 555
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation**Section 3 - Exposure estimation and reference to its source****Website:** : Not applicable.**Exposure estimation and reference to its source - Environment: 1:****Exposure assessment (environment):** : Used ECETOC TRA model.**Exposure estimation and reference to its source** : Not available.**Exposure estimation and reference to its source - Workers: 2:****Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.**Exposure estimation and reference to its source** : Not available.**Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES**

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.