

# LICA 2



Grease



## Multipurpose Lithium/Calcium grease

### APPLICATIONS

**Multi purpose grease**  
**General Lubrication**

**Recommendation**

- **LICA 2** is a multipurpose grease, recommended for the lubrication of the bearings and all mechanical parts in the temperature range from -30 to 110°C .
- Always avoid contamination of the grease by dust and/or dirt when applying. Preferably use a pneumatic pump system or cartridges.

### SPECIFICATIONS

- ISO 6743-9: L-XCCEA2
- DIN 51 502: K2H-30

### ADVANTAGES

**Miscible**  
**Mechanically stable**  
**No harmful substances**

- Because of its true multipurpose character, **LICA 2** may replace a wide range of greases, allowing stock rationalization and simplification of maintenance.

TYPICAL CHARACTERISTICS	METHODS	UNITS	LICA 2
Soap/thickener		-	Lithium/ Calcium
NLGI grade	ASTM D 217/DIN 51 818	-	2
Color	Visual	-	Pale brown
Appearance	Visual	-	Smooth
Operating temperature range		°C	-25 to 120
Penetration at 25°C	ASTM D 217/DIN51 818	0.1 mm	265 - 295
Dropping point	ASTM D 2265	°C	>170°C
Kinematic viscosity of the base oil at 40°C	ASTM D 445/DIN 51 562-1/ISO 3104/IP71	mm <sup>2</sup> /s (cSt)	110

Above characteristics are mean values given as an information.

PT TOTAL OIL INDONESIA  
15-07-2019  
LICA 2  
1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.  
A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser [www.quick-fds.com](http://www.quick-fds.com).

