

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

CERAN XM 220

SDS # : 080100

previous revision date

: 2022/10/19

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: CERAN XM 220

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Lubricating grease

Formulation additives, lubricants and greases - Industrial General use of lubricants and greases in vehicles or machinery - Industrial General use of lubricants and greases in vehicles or machinery - Professional Use of lubricants and greases in open systems - Industrial Use of lubricants and greases in open systems - Professional

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants 562 Avenue du Parc de L'ile 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71 rm.msds-lubs@totalenergies.com

See section 16 to have the contact details of the local supplier

Contact

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number	 France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59 In France - Poison centers: ANGERS : 02 41 48 21 21 BORDEAUX : 05 56 96 40 80 LILLE : 08 00 59 59 59 LYON : 04 72 11 69 11 MARSEILLE : 04 91 75 25 25 NANCY : 03 83 22 50 50 PARIS : 01 40 05 48 48 STRASBOURG : 03 88 37 37 37 TOULOUSE : 05 61 77 74 47
Supplier	E
Telephone number	: Emergency phone: +44 1235 239670



SDS # : 080100

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319

Skin Sens. 1B, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

2

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	: Warning
Hazard statements	 F317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.
Precautionary statements	
Prevention	 ₽261 - Avoid breathing gas, vapor or spray. P280 - Wear protective gloves, protective clothing and eye or face protection.
Response	 P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of soap and water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage	: Not applicable.
Disposal	: Not applicable.
Contains	 Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts Sulfonic acids, petroleum, calcium salts C14-16-18 Alkyl phenol
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %. This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

Other hazards which do : None known. not result in classification



SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/substance	Identifiers	% (w/w)	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	REACH #: 01-2119492627-25 EC: 271-529-4 CAS: 68584-23-6	<10	Skin Sens. 1B, H317	Skin Sens. 1B, H317: C ≥ 10%	[1]
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	REACH #: 01-2119492616-28 EC: 274-263-7 CAS: 70024-69-0	≤3	Skin Sens. 1B, H317	-	[1]
Sulfonic acids, petroleum, calcium salts	REACH #: 01-2119488992-18 EC: 263-093-9 CAS: 61789-86-4	≤3	Skin Sens. 1, H317	Skin Sens. 1, H317: C ≥ 10%	[1]
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	REACH #: 01-2119560592-37 EC: 932-231-6 CAS: 1335202-81-7	<3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412	-	[1]
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	REACH #: 01-2119491299-23 EC: 270-128-1 CAS: 68411-46-1	≤1	Repr. 2, H361f	-	[1]
C14-16-18 Alkyl phenol	REACH #: 01-2119498288-19 EC: 931-468-2	≤0.3	Skin Sens. 1B, H317 STOT RE 2, H373 See Section 16 for the full text of the H	-	[1]
			statements declared above.		

Additional information

: Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.



SECTION 4: First aid measures

4.1 Description of first aid n	neasures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms Eye contact : Adverse symptoms may include the following: pain or irritation watering redness Inhalation : No specific data. : Adverse symptoms may include the following: Skin contact irritation redness dryness cracking Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large
	quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.



SDS #: 080100

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	: No specific fire or explosion hazard.
Hazardous combustion products	: carbon monoxide carbon dioxide nitrogen oxides sulfur oxides Hydrogen sulfide Mercaptans
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	6.1 Personal precautions, protective equipment and emergency procedures				
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.			
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".			
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).			
6.3 Methods and materials for	r c	ontainment and cleaning up			
Small spill	:	Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.			
Large spill	:	Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.			



6.4 Reference to other	: See Section 1 for emergency contact information.
sections	See Section 8 for information on appropriate personal protective equipment.
	See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Reportable hazardous constituent(s) contained in UVCB and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Advisory OEL	:	Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH (TLV) TWA 5 mg/m3 (highly refined)
DNELs/DMELs		

Revision:2023/05/03	Version : 4.01	France	ENGLISH	6/41
---------------------	----------------	--------	---------	------



SDS #: 080100

Product/substance	Туре	Exposure	Value	Population	Effects
Benzenesulfonic acid, C10-16-alkyl	DNEL	Long term Oral	0.8333 mg/	General	Systemic
derivs., calcium salts	DNEL	Long term Dermal	kg bw/day 1.667 mg/	population General	Systemic
	DNEL	Long term Dermal	kg bw/day 3.33 mg/ kg bw/day	population Workers	Systemic
	DNEL	Long term Inhalation	11.75 mg/	Workers	Systemic
	DNEL	Long term Dermal	0.513 mg/ cm ²	General population	Local
	DNEL	Long term Dermal	1.03 mg/ cm²	Workers	Local
	DNEL	Long term Inhalation	2.9 mg/m ³	General population	Systemic
Benzenesulfonic acid, mono- C16-24-alkyl derivs., calcium salts	DNEL	Long term Oral	0.8333 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.667 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	2.9 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	3.33 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	11.75 mg/ m ³	Workers	Systemic
	DNEL	Long term Dermal	0.513 mg/ cm²	General population	Local
	DNEL	Long term Dermal	1.03 mg/ cm²	Workers	Local
Sulfonic acids, petroleum, calcium salts	DNEL	Long term Oral	0.8333 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.667 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	2.9 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	3.33 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	11.75 mg/ m³	Workers	Systemic
	DNEL	Long term Dermal	1.03 mg/ cm²	Workers	Local
	DNEL	Long term Dermal	0.513 mg/ cm²	General population	Local
	DNEL	Long term Dermal	0.513 mg/ cm²	General population	Local
	DNEL	Long term Dermal	1.03 mg/ cm²	Workers	Local
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	DNEL	Long term Dermal	1.7 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	85 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	89 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.7 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	85 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	89 mg/kg bw/day	General population	Systemic



SDS # : 080100

Benzenamine, N-phenyl-, reaction	DNEL	Long term Oral	0.04 mg/	General	Systemic	
products with 2,4,4-trimethylpentene	DNEL	Long term Dermal	kg bw/day 0.04 mg/ kg bw/day	population General population	Systemic	
	DNEL	Long term Dermal	0.08 mg/ kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	0.14 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	0.6 mg/m³	Workers	Systemic	
C14-16-18 Alkyl phenol	DNEL	Long term Inhalation	1.17 mg/m³	Workers	Systemic	
	DNEL	Long term Dermal	0.3 mg/kg bw/day	Workers	Systemic	

PNECs

Product/ingredient name	Compartment Detail	Name	Method Detail
Benzenesulfonic acid, C10-16-alkyl derivs.,	Fresh water	1 mg/l	-
calcium salts	Marina watar	1	
	Marine water	1 mg/l	-
	Fresh water sediment	226000000 mg/	-
		kg dwt	
	Marine water sediment	226000000 mg/	-
	Call	kg dwt	
	Soil	868700000 mg/	-
	Courses Treatment	kg dwt	
	Sewage Treatment	100 mg/l	-
	Plant Community Defension		
	Secondary Poisoning	16.667 mg/kg dwt	-
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	Fresh water	1 mg/l	-
	Marine water	1 mg/l	-
	Fresh water sediment	22600000 mg/	-
		kg dwt	
	Marine water sediment	226000000 mg/	-
		kg dwt	
	Soil	271000000 mg/	-
		kg dwt	
	Sewage Treatment Plant	100 mg/l	-
	Secondary Poisoning	16.667 mg/kg dwt	-
Sulfonic acids, petroleum, calcium salts	Fresh water	1 mg/l	-
	Marine water	1 mg/l	-
	Fresh water sediment	22600000 mg/	-
		kg dwt	
	Marine water sediment	226000000 mg/	-
		kg dwt	
	Soil	271000000 mg/	-
		kg wwt	
	Sewage Treatment	1000 mg/l	-
	Plant	J	
Benzenesulfonic acid, C10-13-alkyl derivs.,	Fresh water	23 µg/l	-
Ca Salt		1.3/	
	Marine water	2.3 µg/l	-
	Sewage Treatment	3 mg/l	-
	Plant		
	Fresh water sediment	174 µg/kg dwt	-
	Marine water sediment	17.4 µg/kg dwt	-
	Soil	620 µg/kg dwt	-
Benzenamine, N-phenyl-, reaction products	Fresh water	33.8 µg/l	-
		100.0 mg/	I



SDS # : 080100

with 2,4,4-trimethylpentene			
	Marine water	3.38 µg/l	-
	Fresh water sediment	446 µg/kg dwt	-
	Marine water sediment	44.6 µg/kg dwt	-
	Soil	1.76 mg/kg dwt	-
C14-16-18 Alkyl phenol	Fresh water	0.1 mg/l	-
	Marine water	0.01 mg/l	-
	Fresh water sediment	4266.16 mg/kg	-
		dwt	
	Marine water sediment	426.62 mg/kg dwt	-
	Soil	852.58 mg/kg dwt	-
	Sewage Treatment	100 mg/l	-
	Plant	-	

Appropriate engineering	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
ndividual protection measu	ires
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.EN 166
Skin protection	
Hand protection	 Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Hydrocarbon-proof gloves nitrile rubber Fluorinated rubber Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its replacement frequency
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be



SDS # :

080100

Respiratory protection	: Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces In case of inadequate ventilation wear respiratory protection: Type A/P1 Warning ! filters have a limited use duration The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties

<u>Appearance</u>			
Physical state	: :	Solid. [grease]	
Color	:	Light brown.	
Odor	: (Characteristic.	
Odor threshold	:	Not available.	
рН	:	Not applicable.	Product is non-soluble (in water).
Melting point/freezing point	: :	>300°C [ISO 3016]	
Initial boiling point and boiling range	:	Not applicable.	
Flash point	:	Not applicable.	
Evaporation rate	:	Not available.	
Flammability	:	Not applicable.	
Lower and upper explosion limit	:	Not applicable.	
Vapor pressure	:	Not applicable.	
Vapor density	:	Not applicable.	
Relative density	: (0.9 [ISO 12185]	
Density	: (0.9 g/cm³ [20°C] [ISO 12185]	
Solubility(ies)	:		
Media		Result	
water		Not soluble	
Miscible with water	:	No.	
Partition coefficient: n-octanol/ water	':	Not applicable.	
Auto-ignition temperature	:	Not applicable.	
Decomposition temperature	: :	>300°C	

Particle characteristicsMedian particle size: Not available.

9.2 Other information

Viscosity

No other relevant physical and chemical parameters for the safe use of the product

: Not applicable.



SECTION 10: Stability and reactivity

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	No specific data.
10.5 Incompatible materials	:	Strong oxidizing agents
10.6 Hazardous decomposition products	:	carbon monoxide carbon dioxide nitrogen oxides sulfur oxides Hydrogen sulfide Mercaptans

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
Penzenesulfonic acid, C10-16-alkyl derivs., calcium salts	LC50 Inhalation Dusts and mists	Rat - Male, Female	>1.9 mg/l	4 hours	EPA OPP 81-3 Acute Inhalation Toxicity
	LD50 Dermal	Rabbit - Male, Female	>4000 mg/kg	-	OECD
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	OECD 401 Read across
Benzenesulfonic acid, mono- C16-24-alkyl derivs., calcium salts	LC50 Inhalation Dusts and mists	Rat - Male, Female	>1.9 mg/l	4 hours	EPA OPP 81-3 Acute Inhalation Toxicity Read across
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	OECD 401
Sulfonic acids, petroleum, calcium salts	LC50 Inhalation Dusts and mists	Rat - Male	>1.9 mg/l	4 hours	EPA OPP 81-3 Acute Inhalation Toxicity
	LD50 Dermal	Rabbit - Male, Female	>4000 mg/kg	-	-
	LD50 Oral	Rat - Male	>16000 mg/ kg	-	Section 772 . 112-21 CFR 40
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-	OECD 402 Read across



SDS # : 080100

C14-16-18 Alkyl phenol	LD50 Dermal LD50 Oral	Rat Rat	2000 mg/kg 2000 mg/kg	-	-
reaction products with 2,4,4-trimethylpentene					
Benzenamine, N-phenyl-,	LD50 Oral LD50 Oral	Rat - Female Rat	4445 mg/kg >5000 mg/kg	-	-

Conclusion/Summary Acute toxicity estimates

Product/substance	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	4445	N/A	N/A	N/A	N/A

Irritation/Corrosion

Product/substance	Result	Species	Score	Exposure	Test
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	Eyes - Cornea opacity	Rabbit	0	-	EPA
	Skin - Edema	Rabbit	0.3	4 hours	EPA OPPTS 870.2500 Acute Dermal Irritation
	Skin - Primary dermal irritation index (PDII)	Rabbit	0.5	4 hours	OECD
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	Eyes - Irritant	Rabbit	1	-	OECD 405
	Skin - Erythema/Eschar	Rabbit	2.7	4 hours	OECD 404

Conclusion/Summary

: Based on available data, the classification criteria are not me	:	Based on	available da	ata. the	classification	criteria are	not met.
-------------------------------------------------------------------	---	----------	--------------	----------	----------------	--------------	----------

: Based on available data, the classification criteria are not met.

: Based on available data, the classification criteria are met.

Respiratory

Skin Eyes

Sensitization

Product/substance	Route of exposure	Species	Result		
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	skin	Human	Sensitizing		
Benzenesulfonic acid, mono- C16-24-alkyl derivs., calcium salts	skin	Mouse	Sensitizing		
Sulfonic acids, petroleum, calcium salts	skin	Guinea pig	Sensitizing		
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	skin	Guinea pig	Not sensitizing		
Conclusion/Summary	:				
Skin	: Based on available data, the classification criteria are not met.				
Respiratory	: Based on avail	: Based on available data, the classification criteria are not met.			
Marte versielter					

Mutagenicity



Product/substance	Test	Experiment	Result
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	OECD 471	Experiment: In vitro Subject: Bacteria	Negative
	OECD 471	Experiment: In vitro Subject: Bacteria	Negative
	OECD 476	Experiment: In vitro Subject: Mammalian-Animal	Negative
	OECD 474	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
	-	Experiment: In vivo Subject: Mammalian-Animal	Negative

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product/substance	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	Negative	Negative	Negative	Rat - Male, Female	Oral	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Product/s	uk	ostance	Category	Route of exposure	Target organs
714-16-18 Alkyl phenol			Category 2	-	-
Conclusion/Summary	:	Based on available data, t	he classification cri	iteria are not met.	
Aspiration hazard					
Conclusion/Summary	:	Based on available data, t	he classification cri	iteria are not met.	
nformation on the likely	:	Not available.			
outes of exposure					
Potential acute health effects					
Eye contact	:	Causes serious eye irritati	on.		
Inhalation	:	No known significant effect	ts or critical hazard	ds.	
Skin contact	:	Defatting to the skin. May skin reaction.	cause skin drynes	s and irritation. N	lay cause an allergic
Ingestion	:	No known significant effect	ts or critical hazard	ds.	

Symptoms related to the physical, chemical and toxicological characteristics



Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Koverse symptoms may include the following: irritation redness dryness cracking
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
<u>Long term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.

Potential chronic health effects

Product/substance	Result	Species	Dose	Exposure		
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	Sub-acute NOAEL Dermal	Rat - Male, Female	>1000 mg/kg	-		
	Sub-acute NOAEL Oral	Rat - Male, Female	500 mg/kg	-		
	Sub-acute NOAEL Inhalation Vapor	Rat - Male, Female	50 mg/m³	28 days		
Conclusion/Summary	: Not available.		·	·		
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.					
Carcinogenicity	: No known significant effects or critical hazards.					
Mutagenicity	: No known significant effects	: No known significant effects or critical hazards.				
Reproductive toxicity	: No known significant effects	s or critical hazard	S.			

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information

Not available.



SECTION 12: Ecological information

12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	Acute EC50 >1000 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Acute EC50 >1000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute LC50 >1000 mg/l	Fish - Cyprinodon variegatus	96 hours	OECD 203
	Chronic EC10 >1000 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
Benzenesulfonic acid, mono- C16-24-alkyl derivs., calcium salts	Acute EC50 >1000 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Acute EC50 >1000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute LC50 >1000 mg/l	Fish - Cyprinodon variegatus	96 hours	OECD 203
	Chronic EC10 >1000 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
Sulfonic acids, petroleum, calcium salts	Acute EC50 >1000 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Acute EC50 >1000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute LC50 >1000 mg/l	Fish - Cyprinodon variegatus	96 hours	OECD 203
	Chronic EC10 >1000 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	Acute EC50 29 mg/l	Algae - Pseudokirchneriella subcapitata	96 hours	STDMETH, ASTM and USEPA 201
	Acute EC50 2.9 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute LC50 1.67 mg/l	Fish - Lepomis macrochirus	96 hours	STDMETH, ASTM and USEPA
	Chronic NOEC 0.5 mg/l	Algae - Pseudokirchneriella subcapitata	96 hours	STDMETH, ASTM and USEPA 201
	Chronic NOEC 0.379 mg/l	Daphnia	48 hours	OECD 211
C14-16-18 Alkyl phenol	Acute EC50 >100 mg/l	Daphnia - Daphnia magna	48 hours	OECD 202

12.2 Persistence and degradability



SDS # : 080100

Product/substance	Test	Result	Dose	Inoculum
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	OECD 301D	0 % - Not readily - 28 days	-	Activated sludge
Benzenesulfonic acid, mono- C16-24-alkyl derivs., calcium salts	OECD 301D	0 % - Not readily - 28 days	-	Activated sludge
Sulfonic acids, petroleum, calcium salts	OECD 301D	0 % - Not readily - 28 days	-	Activated sludge
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	OECD 301B	>90 % - Readily - 28 days	-	Activated sludge

Conclusion/Summary : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Benzenesulfonic acid,	-	-	Not readily
C10-16-alkyl derivs.,			
calcium salts			
Benzenesulfonic acid, mono-	-	-	Not readily
C16-24-alkyl derivs.,			
calcium salts			
Sulfonic acids, petroleum,	-	-	Not readily
calcium salts			
Benzenesulfonic acid,	-	-	Readily
C10-13-alkyl derivs., Ca Salt			
Benzenamine, N-phenyl-,	-	-	Not readily
reaction products with			
2,4,4-trimethylpentene			

12.3 Bioaccumulative potential

Product/substance	LogKow	BCF	Potential
Penzenesulfonic acid, C10-16-alkyl derivs., calcium salts	22	-	high
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	2.89	-	low
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	5.1	1730	high

12.4 Mobility in soil	
Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.
Mobility in soil	: Given its physical and chemical characteristics, the product has no soil mobility. The product is insoluble and floats on water Loss by evaporation is limited

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %.

12.6 Endocrine disrupting properties

Revision:2023/05/03	Version : 4.01



This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used The following Waste Codes are only suggestions: 12 01 12*
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.



14.7 Maritime transport in : Not available. **bulk according to IMO instruments**

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Take note of Dir 94/33/EC on the protection of young people at work. Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Industrial emissions
(integrated pollution
prevention and control) -
Air: Not listedIndustrial emissions
(integrated pollution
prevention and control) -
Water: Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

	Mineral oil	RG36
Reinforced medical surveillance	: Decree n ° 2012-135 of Janua occupational medicine: not ap	ary 30, 2012 relating to the organization of plicable
Other regulations	dangerous chemical agents.	ne Labor Code relating to the provisions applicable to ode relating to young workers.



International regulations Chemical Weapon Convention List Schedules I, Not listed.	II & III Chemicals
Montreal Protocol Not listed.	
Stockholm Convention on Persistent Organic Po Not listed.	<u>ollutants</u>
Rotterdam Convention on Prior Informed Conservation Not listed.	nt (PIC)
UNECE Aarhus Protocol on POPs and Heavy Me Not listed.	<u>tals</u>
LU - Luxembourg prohibited chemicals in the work Not listed.	<u>prkplace</u>
Inventory list	
Australia inventory (AIIC)	: All components are listed or exempted.
Canada inventory (DSL/NDSL)	: All components are listed or exempted.
China inventory (IECSC)	: All components are listed or exempted.
Europe inventory (EC)	: All components are listed or exempted.
Japan inventory	 Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC)	: Not determined.
Philippines inventory (PICCS)	: All components are listed or exempted.
Korea inventory (KECI)	: All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	: All components are listed or exempted.
Thailand inventory	: Not determined.
Turkey inventory	: Not determined.
United States inventory (TSCA 8b)	: All components are listed or exempted.
Vietnam inventory	: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical Safety : See exposure scenarios **Assessment**



SDS #: 080100

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level DMEL = Derived Minimal Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic vPvB = Very Persistent and Very Bioaccumulative PNEC = Predicted No Effect Concentration LC50 = Median lethal concentration LD50 = Median lethal dose OEL = Occupational Exposure Limit VOC = Volatile Organic Compound UVCB Substance of unknown or Variable composition, Complex reaction products or Biological material NOEC No Observed Effect Concentration
	NOEC No Observed Effect Concentration QSAR = Quantitative Structure–Activity Relationship

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
	Calculation method Calculation method

Full text of abbreviated H statements

⊮ 315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Aquatic Chronic 3 Eye Dam. 1	AQUATIC HAZARD (LONG-TERM) - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Repr. 2 Skin Irrit. 2	TOXIC TO REPRODUCTION - Category 2 SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

Additionnal details on the supplier of the product

TotalEnergies Marketing Antilles-Guyane ZI. Californie 97232 Le Lamentin Martinique France Tel: +596 596 504 957



SDS # : 080100

TotalEnergies Marketing Mayotte
Immeuble Jacaranda 1, Lotissement Les 3 vallées Majicavo Lamir
BP 867 kawéni
97600 MAMOUDZOU
tél : +262 (0) 269 60 12 94
fax : +262 (0) 269 60 17 30

TotalEnergies Marketing Réunion 3 rue Jacques Prévert BP286 – 97827 LE PORT tél : +262 (0) 262 55 20 20 fax : +262 (0) 262 55 20 31

Date of revision	: 2023/05/03
previous revision date	: 2022/10/19
Version	: 4.01

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture		
Product definition	:	Mixture
Code	:	080100
Product name	1	CERAN XM 220
Section 1 - Title		
Short title of the exposure scenario	:	Use of lubricants and greases in open systems - Professional
List of use descriptors	:	Identified use name: Use of lubricants and greases in open systems - Professional Process Category: PROC01, PROC02, PROC08a, PROC10, PROC11, PROC13 Sector of end use: SU22 Subsequent service life relevant for that use: No. Environmental Release Category: ERC08a, ERC08d
Environmental contributing scenarios	:	
Health Contributing scenarios	:	General measures applicable to all activities Material transfers Manual - PROC08a Roller, spreader, flow application - PROC10 Spraying - PROC11 Treatment of articles by dipping and pouring - PROC13 Equipment cleaning and maintenance - PROC08a Storage - PROC01, PROC02
Processes and activities covered by the exposure scenario	:	Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mold releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.

Section 2 - Exposure controls

Contributing scenario contro No exposure scenario require		ng environmental exposure for 1:
Contributing scenario contro	lli	ng worker exposure for 2: General measures applicable to all activities
Concentration of substance in mixture or article	:	Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	:	Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure.
Frequency and duration of use/exposure	:	Covers daily exposures up to 8 hours (unless stated differently).
Other conditions affecting workers exposure	1	Assumes use at not more than 20°C above ambient temperature. unless stated differently. Assumes a good basic standard of occupational hygiene has been implemented.
Conditions and measures rel	ate	ed to personal protection, hygiene and health evaluation
Advice on general occupational hygiene	:	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	1	Use suitable eye protection.

CERAN XM 220	- Use of lubricants and greases in open systems Professional
Contributing scenario contro	olling worker exposure for 3: Material transfers Manual
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Contributing scenario contro	olling worker exposure for 4: Roller, spreader, flow application
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour) Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Contributing scenario contro	olling worker exposure for 5: Spraying
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour) Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Personal protection	: Wear suitable coveralls to prevent exposure to the skin. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Respiratory protection	: Wear a respirator conforming to EN140 with type A/P2 filter or better.
Contributing scenario contro	olling worker exposure for 6: Treatment of articles by dipping and pouring
Ventilation control measures	: Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour) Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Contributing scenario contro	olling worker exposure for 7: Equipment cleaning and maintenance
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Technical conditions and measures at process level (source) to prevent release	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down system prior to equipment break-in or maintenance.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour) Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Contributing scenario contro	olling worker exposure for 8: Storage
Engineering controls	: Store substance within a closed system.
	lated to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website:	: Not applicable.	
Exposure estimation and reference to its source - Environment: 1:		
Exposure assessment (environment):	: Used ECETOC TRA model.	
Exposure estimation and reference to its source	: Not available.	

CERAN XM 220	- Use of lubricants and greases in open systems Professional
Exposure estimation and ref	ference to its source - Workers: 2: General measures applicable to all activities
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 3: Material transfers Manual
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and re	ference to its source - Workers: 4: Roller, spreader, flow application
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 5: Spraying
Exposure assessment (human):	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 6: Treatment of articles by dipping and pouring
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ret	ference to its source - Workers: 7: Equipment cleaning and maintenance
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 8: Storage
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	 Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

CERAN XM 220		- Use of lubricants and greases in open systems Professional
Environment	: Not available.	
Health	: Not available.	

Annex to the extended Safety Data Sheet (eSDS)

Identification of the substance or mixture **Product definition** : Mixture : 080100 Code : CERAN XM 220 **Product name** Section 1 - Title Short title of the exposure : Use of lubricants and greases in open systems - Industrial scenario List of use descriptors : Identified use name: Use of lubricants and greases in open systems - Industrial Process Category: PROC01, PROC02, PROC07, PROC08b, PROC09, PROC10, PROC13 Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC04 **Environmental contributing** : scenarios **Health Contributing** : General measures applicable to all activities Material transfers Manual - PROC08b scenarios Material transfers Automated process with (semi) closed systems - PROC08b, PROC09 Roller, spreader, flow application - PROC10 Spraying - PROC07 Treatment of articles by dipping and pouring - PROC13 Equipment cleaning and maintenance - PROC08b Storage - PROC01, PROC02 **Processes and activities** Covers use of lubricants and greases in open systems, including application of 2 lubricant to work pieces or equipment by dipping, brushing or spraying (without covered by the exposure exposure to heat), e.g. mold releases, corrosion protection, slideways. Includes scenario associated product storage, material transfers, sampling and maintenance activities

Section 2 - Exposure controls

Contributing scenario contro No exposure scenario require		ng environmental exposure for 1:	
Contributing scenario contro	olli	ng worker exposure for 2: General measures applicable to all activities	
Concentration of substance in mixture or article	:	Covers percentage substance in the product up to 100% (unless stated differe	ntly).
Physical state	1	Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure.	
Frequency and duration of use/exposure	:	Covers daily exposures up to 8 hours (unless stated differently).	
Other conditions affecting workers exposure	:	Assumes use at not more than 20°C above ambient temperature. unless state differently. Assumes a good basic standard of occupational hygiene has been implemented	
Conditions and measures re	lat	ed to personal protection, hygiene and health evaluation	
Advice on general occupational hygiene	:	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures a report any skin problems that may develop. Other skin protection measures su impervious suits and face shields may be required during high dispersion activ which are likely to lead to substantial aerosol release, e.g. spraying. Avoid direct contact with product, also via contamination on hands.	n and to ich as ities
Date of issue/Date of revisio	n	: 7/7/2020	26/4 ⁻

Industrial

CERAN XM 220	- Use of lubricants and greases in open systems Industrial
Personal protection	: Use suitable eye protection.
Contributing scenario contro	Iling worker exposure for 3: Material transfers Manual
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
Conditions and measures rel	ated to personal protection, hygiene and health evaluation
Contributing scenario contro closed systems	Iling worker exposure for 4: Material transfers Automated process with (semi)
Ventilation control measures	: Ensure material transfers are under containment or extract ventilation.
Conditions and measures rel	ated to personal protection, hygiene and health evaluation
Contributing scenario contro	Iling worker exposure for 5: Roller, spreader, flow application
Ventilation control measures	: Provide extract ventilation to points where emissions occur.
Conditions and measures rel	ated to personal protection, hygiene and health evaluation
Contributing scenario contro	Iling worker exposure for 6: Spraying
Ventilation control measures	: Carry out in a vented booth or extracted enclosure.
Conditions and measures rel	ated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Contributing scenario contro	Iling worker exposure for 7: Treatment of articles by dipping and pouring
Ventilation control measures	: Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour)
Conditions and measures rel	ated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Contributing scenario contro	Iling worker exposure for 8: Equipment cleaning and maintenance
Technical conditions and measures at process level (source) to prevent release	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down system prior to equipment break-in or maintenance.
Ventilation control measures	 Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
Conditions and measures rel	ated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Contributing scenario contro	Iling worker exposure for 9: Storage
Engineering controls	: Store substance within a closed system.
Conditions and measures rel	ated to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website:	: Not applicable.	
Exposure estimation and reference to its source - Environment: 1:		
Exposure assessment (environment):	: Used ECETOC TRA model.	
Exposure estimation and reference to its source	: Not available.	

CERAN XM 220	Use of lubricants and greases in open systems Industria
Exposure estimation and re	ference to its source - Workers: 2: General measures applicable to all activities
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and re	ference to its source - Workers: 3: Material transfers Manual
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and read (semi) closed systems	ference to its source - Workers: 4: Material transfers Automated process with
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and re	ference to its source - Workers: 5: Roller, spreader, flow application
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and re	ference to its source - Workers: 6: Spraying
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and re	ference to its source - Workers: 7: Treatment of articles by dipping and pouring
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ret	ference to its source - Workers: 8: Equipment cleaning and maintenance
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and re	ference to its source - Workers: 9: Storage
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

CERAN XM 220	- Use of lubricants and greases in open systems Industrial
Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Identification of the substance or mixture **Product definition** : Mixture : 080100 Code : CERAN XM 220 **Product name** Section 1 - Title Short title of the exposure : Formulation additives, lubricants and greases - Industrial scenario List of use descriptors : Identified use name: Formulation additives, lubricants and greases - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15 Sector of end use: SU03, SU10 Subsequent service life relevant for that use: No. Environmental Release Category: ERC02 **Environmental contributing** : scenarios **Health Contributing** : General measures applicable to all activities General exposures Use in contained systems Elevated temperature - PROC02 scenarios Mixing operations Closed systems Batch processes at elevated temperatures -PROC03 Mixing operations Open systems Batch processes at elevated temperatures -PROC04, PROC05 Mixing operations (open systems) - PROC04, PROC05 Process sampling - PROC04, PROC08b Bulk transfers Dedicated facility - PROC08b Drum/batch transfers Dedicated facility - PROC08b Drum/batch transfers Non-dedicated facility - PROC08a Equipment cleaning and maintenance - PROC08a, PROC08b Drum and small package filling - PROC09 Laboratory activities - PROC15 Storage - PROC01, PROC02 **Processes and activities** : Industrial formulation of lubricant additives, lubricants and greases. Includes material transfers, mixing, large and small scale packing, sampling, maintenance. covered by the exposure scenario

Section 2 - Exposure controls

Contributing scenario contro No exposure scenario require		ng environmental exposure for 1:	
Contributing scenario contr	olliı	ng worker exposure for 2: General measures applicable to all activities	
Concentration of substance in mixture or article	:	Covers percentage substance in the product up to 100 %. (unless stated differen	itly)
Physical state	:	Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure	
Amounts used	:	Not applicable.	
Frequency and duration of use/exposure	1	Covers daily exposures up to 8 hours (unless stated differently)	
Human factors not influenced by risk management	:	Not applicable.	
Other conditions affecting workers exposure	:	Covers percentage substance in the product up to 100% (unless stated differently	y)
Date of issue/Date of revisio	n	: 7/2/2020 3	80/4 ⁻

Industrial

CERAN XM 220	- Formulation additives, lubricants and greases Industrial
Conditions and measures rela	ted to personal protection, hygiene and health evaluation
occupational hygiene	: Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	: Use suitable eye protection.
Elevated temperature	ling worker exposure for 3: General exposures Use in contained systems
No other specific measures ide	
Conditions and measures rela	ted to personal protection, hygiene and health evaluation
Contributing scenario controll at elevated temperatures	ling worker exposure for 4: Mixing operations Closed systems Batch processes
Ventilation control measures	: Provide extract ventilation to points where emissions occur.
Conditions and measures rela	ted to personal protection, hygiene and health evaluation
Contributing scenario controll elevated temperatures	ling worker exposure for 5: Mixing operations Open systems Batch processes at
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Ventilation control measures	: Provide extract ventilation to points where emissions occur.
Conditions and measures rela	ted to personal protection, hygiene and health evaluation
Contributing scenario controll	ling worker exposure for 6: Mixing operations (open systems)
Ventilation control measures	: Provide extract ventilation to points where emissions occur.
Conditions and measures rela	ted to personal protection, hygiene and health evaluation
Contributing scenario controll	ling worker exposure for 7: Process sampling
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
Conditions and measures rela	ted to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Contributing scenario controll	ling worker exposure for 8: Bulk transfers Dedicated facility
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Conditions and measures rela	ted to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Contributing scenario controll	ling worker exposure for 9: Drum/batch transfers Dedicated facility
Ventilation control measures	: Provide extract ventilation to points where emissions occur.
Conditions and measures rela	ted to personal protection, hygiene and health evaluation

CERAN XM 220	Formulation additives, lubricants and greases Industria
Contributing scenario contr	olling worker exposure for 10: Drum/batch transfers Non-dedicated facility
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Contributing scenario contri	olling worker exposure for 11: Equipment cleaning and maintenance
Technical conditions and measures to control dispersion from source towards the worker	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down and flush system prior to equipment break-in or maintenance.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Advice on general occupational hygiene	: Clear spills immediately.
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Contributing scenario contr	olling worker exposure for 12: Drum and small package filling
Ventilation control measures	: Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Contributing scenario contr	olling worker exposure for 13: Laboratory activities
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Contributing scenario contr	olling worker exposure for 14: Storage
Engineering controls	: Store substance within a closed system.
Conditions and measures re	lated to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website:	:	Not applicable.
Exposure estimation and ref	ere	nce to its source - Environment: 1:
Exposure assessment (environment):	:	Used ECETOC TRA model.
Exposure estimation and reference to its source	:	Not available.
Exposure estimation and ref	ere	nce to its source - Workers: 2: General measures applicable to all activities
Exposure assessment (human):	:	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	:	Not available.

CERAN XM 220	- Formulation additives, lubricants and greases Industrial
Exposure estimation and ref	ference to its source - Workers: 3: General exposures Use in contained systems
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref processes at elevated tempe	erence to its source - Workers: 4: Mixing operations Closed systems Batch eratures
Exposure assessment (human):	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref processes at elevated tempe	erence to its source - Workers: 5: Mixing operations Open systems Batch eratures
Exposure assessment (human):	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 6: Mixing operations (open systems)
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 7: Process sampling
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 8: Bulk transfers Dedicated facility
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 9: Drum/batch transfers Dedicated facility
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 10: Drum/batch transfers Non-dedicated facility
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

CERAN XM 220	- Formulation additives, lubricants and greases Industrial
Exposure estimation and ref	ference to its source - Workers: 11: Equipment cleaning and maintenance
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 12: Drum and small package filling
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 13: Laboratory activities
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 14: Storage
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment	: Not available.	
Health	: Not available.	

Annex to the extended Safety Data Sheet (eSDS)

Product definition : Mixture : 080100 Code : CERAN XM 220 **Product name** Section 1 - Title Short title of the exposure : General use of lubricants and greases in vehicles or machinery - Industrial scenario List of use descriptors : Identified use name: General use of lubricants and greases in vehicles or machinery - Industrial Process Category: PROC01, PROC02, PROC08b, PROC09 Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC04, ERC07 **Environmental contributing** : scenarios **Health Contributing** : General measures applicable to all activities General exposures (closed systems) - PROC01 scenarios Initial factory fill of equipment Use in contained systems - PROC02, PROC09 Initial factory fill of equipment Open systems - PROC08b Operation of equipment containing engine oils and similar Use in contained systems - PROC01 Equipment cleaning and maintenance - PROC08b Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature) - PROC08b Storage - PROC01, PROC02 **Processes and activities** 2 Covers general use of lubricants and greases in vehiculs or machinery in closed covered by the exposure systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities. scenario

Section 2 - Exposure controls

Date of issue/Date of revision : 7/6/2020

Contributing scenario contro No exposure scenario require	blling environmental exposure for 1: ed
Contributing scenario contri	olling worker exposure for 2: General measures applicable to all activities
Concentration of substance in mixture or article	: Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	: Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure.
Frequency and duration of use/exposure	: Covers daily exposures up to 8 hours (unless stated differently).
Other conditions affecting workers exposure	 Assumes use at not more than 20°C above ambient temperature. unless stated differently. Assumes a good basic standard of occupational hygiene has been implemented.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Advice on general occupational hygiene	: Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	: Use suitable eye protection.

Identification of the substance or mixture

Industrial

CERAN XM 220	General use of lubricants and greases in vehicles of machinery - Industria
No other specific measures	
Conditions and measures r	elated to personal protection, hygiene and health evaluation
systems No other specific measures	rolling worker exposure for 4: Initial factory fill of equipment Use in contained identified. elated to personal protection, hygiene and health evaluation
Contributing scenario contributing scenario contributing Frequency and duration of use/exposure	 rolling worker exposure for 5: Initial factory fill of equipment Open systems Avoid carrying out activities involving exposure for more than 4 hours per day.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour)
Conditions and measures r	elated to personal protection, hygiene and health evaluation
similar Use in contained sys	
No other specific measures Conditions and measures re	identified. elated to personal protection, hygiene and health evaluation
Contributing scenario cont	rolling worker exposure for 7: Equipment cleaning and maintenance
Technical conditions and measures at process level (source) to prevent release	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down system prior to equipment break-in or maintenance.
Ventilation control measures	: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
Conditions and measures r	elated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
	rolling worker exposure for 8: Equipment cleaning and maintenance Operation is perature (> 20°C above ambient temperature)
Technical conditions and measures to control dispersion from source towards the worker	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down system prior to equipment break-in or maintenance.
Ventilation control measures	 Provide extract ventilation to emission points when contact with warm (>50°C) lubricant is likely.
	elated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Contributing scenario cont	rolling worker exposure for 9: Storage
Engineering controls	: Store substance within a closed system.
Conditions and massures r	elated to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website:	: Not applicable.	
Exposure estimation and reference to its source - Environment: 1:		
Exposure assessment (environment):	: Used ECETOC TRA model.	
Exposure estimation and reference to its source	: Not available.	

CERAN XM 220	General use of lubricants and greases in vehicles or machinery - Industrial
Exposure estimation and ref	erence to its source - Workers: 2: General measures applicable to all activities
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 3: General exposures (closed systems)
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 4: Initial factory fill of equipment Use in contained
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 5: Initial factory fill of equipment Open systems
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref and similar Use in contained	erence to its source - Workers: 6: Operation of equipment containing engine oils I systems
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 7: Equipment cleaning and maintenance
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
	erence to its source - Workers: 8: Equipment cleaning and maintenance Operation nperature (> 20°C above ambient temperature)
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 9: Storage
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

CERAN XM 220	General use of lubricants and greases in vehicles or machinery - Industrial
Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Identification of the substance or mixture

Professional

Product definition	:	Mixture
Code	:	080100
Product name	:	CERAN XM 220
Section 1 - Title		
Short title of the exposure scenario	1	General use of lubricants and greases in vehicles or machinery - Professional
List of use descriptors	1	Identified use name: General use of lubricants and greases in vehicles or machinery - Professional
		Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20 Sector of end use: SU22
		Subsequent service life relevant for that use: No.
		Environmental Release Category: ERC09a, ERC09b
Environmental contributing scenarios	1	
Health Contributing scenarios	:	General measures applicable to all activities Operation of equipment containing engine oils and similar Use in contained systems - PROC01
		Material transfers Non-dedicated facility - PROC08a Equipment cleaning and maintenance Dedicated facility - PROC08b, PROC20 Storage - PROC01, PROC02
Processes and activities covered by the exposure scenario	:	Covers general use of lubricants and greases in vehiculs or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

Section 2 - Exposure controls

Contributing scenario contro No exposure scenario require		ng environmental exposure for 1:
Contributing scenario contro	ollir	ng worker exposure for 2: General measures applicable to all activities
Concentration of substance in mixture or article	-	Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	:	Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure.
Frequency and duration of use/exposure	:	Covers daily exposures up to 8 hours (unless stated differently).
Other conditions affecting workers exposure	:	Assumes use at not more than 20°C above ambient temperature. unless stated differently. Assumes a good basic standard of occupational hygiene has been implemented.
Conditions and measures re	late	ed to personal protection, hygiene and health evaluation
Advice on general occupational hygiene	:	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	:	Use suitable eye protection.

CERAN XM 220	General use of lubricants and greases in vehicles or machinery - Professional
Contributing scenario controll similar Use in contained syste No other specific measures ide	
•	ted to personal protection, hygiene and health evaluation
	ted to personal protection, hygiche and nearth evaluation
Contributing scenario controll	ing worker exposure for 4: Material transfers Non-dedicated facility
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Conditions and measures rela	ted to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Contributing scenario controll facility	ing worker exposure for 5: Equipment cleaning and maintenance Dedicated
Technical conditions and measures at process level (source) to prevent release	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down system prior to equipment break-in or maintenance.
Conditions and measures rela	ted to personal protection, hygiene and health evaluation
Contributing scenario controll	ing worker exposure for 6: Storage
Engineering controls	: Store substance within a closed system.
Conditions and measures rela	ted to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website:	: Not applicable.		
Exposure estimation and ref	Exposure estimation and reference to its source - Environment: 1:		
Exposure assessment (environment):	: Used ECETOC TRA model.		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and ref	erence to its source - Workers: 2: General measures applicable to all activities		
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and ref and similar Use in contained	erence to its source - Workers: 3: Operation of equipment containing engine oils systems		
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and ref	erence to its source - Workers: 4: Material transfers Non-dedicated facility		
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.		
Exposure estimation and reference to its source	: Not available.		

CERAN XM 220	General use of lubricants and greases in vehicles or machinery - Professional
Exposure estimation and ref	ference to its source - Workers: 5: Equipment cleaning and maintenance Dedicated
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ret	ference to its source - Workers: 6: Storage
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.